

www.pfcstore.com - 763-425-7890 / 800-328-2350



## MOYNO® SANITARY PUMP SINGLE STAGE, STAINLESS STEEL WITH EPDM

**CONTACT US FOR PRICING** | .75  
GPM Per 100 RPM, Max 87 PSI Data  
based on water @ 68F, Cast Iron,  
Stator EPDM 70 Durometer, Tri-  
clamp connections, Single Mech  
Seal Car/Ceramic, Rotor Chrome  
Plated, 1 hp 3/60/230-460v Gear  
Motor wash down 5:1 turn down,  
Close Coupled Mounted on  
Stainless Base. Product photo  
could vary from the actual product



---

**SKU:** FB1BSSB3SBA

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Progressing Cavity  
Pumps](#)

**Model Number** Sanitary 1000  
**Part Number** FB1BSSB3SBA

www.pfcestore.com - 763-425-7890 / 800-328-2350

## PRODUCT DESCRIPTION

### **Moyno® Sanitary Pumps**

Low-shear, non-pulsating Sanitary Pumps transfer shear-sensitive materials with a minimum of turbulence or stress.

#### **Features**

Mechanical seals standard

Standard models meet 3A and BISSC sanitary requirements with no modifications

Close-coupled and open throat models

#### **Performance Features**

Minimal product degradation in shear-sensitive applications

Long service life in abrasive slurries and corrosive fluids

Temperatures to 350° F, viscosities to 1,000,000 cps

Handle suspended solids to 1.1" diameter

Pressures to 225 psi; capacities from .02 to 345 gpm

#### **Typical Applications**

Bread dough & bakery products

Sauces, juices & jellies

Meat & dairy products

Wine

Yogurt

Chemical feed

Estimated delivery is 6 to 10 weeks

Contact us for actual Lead times

Product photo could vary from the actual product

[Sanitary Curve](#)

[Sanitary Dimensions](#)

[Sanitary Service Manual](#)

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

**Our Moyno area covers Minnesota, Wisconsin, South Dakota, North Dakota & the U.P. Michigan**

## ADDITIONAL INFORMATION

<b>Weight</b>	250 lbs
<b>Dimensions</b>	40 × 22 × 17 in
<b>Recommended RPM</b>	100 RPM to 400 RPM

**CONTACT US FOR PRICING** | .75 GPM Per 100 RPM, Max 87 PSI Data based on water @ 68F, Cast Iron, Stator EPDM 70 Durometer, Tri-clamp connections, Single Mech Seal Car/Ceramic, Rotor Chrome Plated, 1 hp 3/60/230-460v Gear Motor wash down 5:1 turn down, Close Coupled Mounted on Stainless Base. Product photo could vary from the actual product