

www.pfcstore.com - 763-425-7890 / 800-328-2350



SEAMETRICS FLANGED MAGMETER, 2" FLANGE

Flange 2" 150lb Ansi | Gaskets non-NSF | 9-36 Vdc @ 250 mA max, 30 mA average | Outputs: One Pulse, One 4-20mA | Liner Polyurethane / Noryl | Body Welded steel, epoxy-coated



SKU: IMAG4700P-0200-F1-R-D1-X-XX-0000

Stock: Out of stock contact us for lead time

Categories: [Seametrics](#)
[Magmeters](#)

Part Number IMAG4700P-0200-F1-R-D1-X-XX-0000

PRODUCT DESCRIPTION

Seametrics magmeters are CE certified, certified to NSF/ANSI standard 61 and are rated IP68 for applications where the meter may be operated under water to a depth of at least 10 feet (3 meters) continuously.

Estimated delivery 2 to 4 weeks

www.pfcstore.com - 763-425-7890 / 800-328-2350

[Specs](#)

[Manual](#)

[Quick Start](#)

ADDITIONAL INFORMATION

Weight	25 lbs
Dimensions	12 × 8 × 16 in

Flange 2" 150lb Ansi | Gaskets non-NSF | 9-36 Vdc @ 250 mA max, 30 mA average | Outputs: One Pulse, One 4-20mA | Liner Polyurethane / Noryl | Body Welded steel, epoxy-coated