


www.pfcstore.com - 763-425-7890 / 800-328-2350



## SEAMETRICS FLANGED MAGMETER, 3" FLANGE

Flange 3" 150lb Ansi | Gaskets non-NSF | 9-36 Vdc @ 250 mA max, 30 mA average | Outputs: One Pulse, One 4-20mA | Liner Polyurethane / Noryl | Body Welded steel, epoxy-coated



**SKU:** IMAG4700P-0300-F1-R-D1-X-XX-0000

**Stock:** Out of stock contact us for lead time

**Categories:** [Seametrics](#)  
[Magmeters](#)

**Part Number** IMAG4700P-0300-F1-R-D1-X-XX-0000

## PRODUCT DESCRIPTION

Seametrics magmeters are CE certified, certified to NSF/ANSI standard 61 and are rated IP68 for applications where the meter may be operated under water to a depth of at least 10 feet (3 meters) continuously.

**Estimated delivery 2 to 4 weeks**

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

[Specs](#)

[Manual](#)

[Quick Start](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	25 lbs
<b>Dimensions</b>	12 × 9 × 16 in

Flange 3" 150lb Ansi | Gaskets non-NSF | 9-36 Vdc @ 250 mA max, 30 mA average | Outputs: One Pulse, One 4-20mA | Liner Polyurethane / Noryl | Body Welded steel, epoxy-coated