



## SHELCO STRING WOUND FDA BLEACHED COTTON, 316SS CORE, 1 MICRON, 20" LENGTH

**Qty 1 equals 15 filters per case** | 1 Micron | Length 20" | Max Diameter 2.5" | Double Open End | Max Temp 250°F



---

**SKU:** MS20CG1

**Stock:** 103 in stock

**Categories:** [Cartridge Filters](#),  
[Inventory Sale!](#)

**Part Number** MS20CG1

## PRODUCT DESCRIPTION

- Shelco string wound recognized as the industry standard for high quality wound filters – these filter cartridges last 2-3 times longer than standard melt-blown or spun bond cartridges
- Computerized production machinery produces precise geometric patterns to ensure high efficiency, superior dirt-holding capacity and repeatable performance
- Wide range of media and core materials to meet most temperature and chemical compatibility requirements

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

- Available in 0.5 – 150 micron ratings
- Ideal for removing solids from liquids, compressed air or gases
- Independently tested to have the highest efficiencies in the industry

Contact us for special order filters

Estimated delivery is 1 to 4 days

Contact us for actual lead time

Product photo could vary from the actual product

[String Wound Specs](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	25 lbs
<b>Dimensions</b>	21 × 12.50 × 12.50 in
<b>Manufacturer</b>	<a href="#"><u>Sheclo String Wound Filter</u></a>