



SHELCO STRING WOUND NATURAL COTTON/POLYPROPYLENE CORE CARTRIDGE MS10

Qty 1 equals 30 filters per case | 50 Micron | Length 10" | Max Diameter 2.5" | Double Open End | Max Temp 140°F



SKU: MS10UP50

Stock: Out of stock contact us for lead time

Categories: [Cartridge Filters](#)

Tags: [Shelco Filters](#)

Part Number MS10UP50

PRODUCT DESCRIPTION

- Shelco string wound recognized as the industry standard for high quality wound filters – these filter cartridges last 2-3 times longer than standard melt-blown or spun bond cartridges
- Computerized production machinery produces precise geometric patterns to ensure high efficiency, superior dirt-holding capacity and repeatable performance
- Wide range of media and core materials to meet most temperature and chemical compatibility requirements

www.pfcstore.com - 763-425-7890 / 800-328-2350

- Available in 0.5 – 150 micron ratings
- Ideal for removing solids from liquids, compressed air or gases
- Independently tested to have the highest efficiencies in the industry

Contact us for special order filters

Estimated delivery is 1 to 4 days

Contact us for actual lead time

Product photo could vary from the actual product

[String Wound Specs](#)

ADDITIONAL INFORMATION

Weight	20 lbs
Dimensions	11 × 15 × 12.50 in
Connections	<u>Double Open End</u>
Length	<u>10"</u>
Micron	<u>50</u>
Wetted Material	<u>Natural Cotton/Polypro Core</u>