



SUMMIT 2196 ANSI PUMP, 316SS, 1.5 X 3 - 6 STO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller:
3600rpm 175GPM @ 135FTH |
1800rpm 100GPM @ 33FTH |
SF18103 Standard Bore Cartridge
Seal C/SC/V/316SS

316SS PUMPS HAVE AN 316SS
CASING AND STUFFING BOX
COVER; A 316SS IMPELLER AND
SLEEVE; AND A 4140 SHAFT.



SKU: 2196STO, 1.5X3-6-316SS-
SF18103

Stock: Out of stock contact us for
lead time

Categories: [Summit 2196 Ansi
Pumps](#)

PRODUCT DESCRIPTION

www.pfcstore.com - 763-425-7890 / 800-328-2350

Summit 2196 Pump, Features

- Rear Pull-Out Design
- Efficient Interchangeable Parts
 - Capacities to 6000 GPM
 - Heads to 730 feet
- Temperatures to 700 deg F
 - Fully Open Impeller
- Extra Large Oil Sump
 - Rigid Frame Foot

Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

Typical lead time 2 to 4 weeks

[3600RPM Curve](#)

[1800RPM Curve](#)

[Summit Brochure](#)

[Summit Manual](#)

ADDITIONAL INFORMATION

Weight	110 lbs
Dimensions	24 × 14 × 18 in
Best Efficiency Point	<u>100 GPM @ 35 FTH, 175 GPM @ 125 FTH</u>
Wetted Material	<u>316SS-VITON</u>

www.pfcestore.com - 763-425-7890 / 800-328-2350

Best Efficiency Point Full Impeller: 3600rpm 175GPM @ 135FTH | 1800rpm
100GPM @ 33FTH | SF18103 Standard Bore Cartridge Seal C/SC/V/316SS

316SS PUMPS HAVE AN 316SS CASING AND STUFFING BOX COVER; A 316SS
IMPELLER AND SLEEVE; AND A 4140 SHAFT.