



## SUMMIT 2196 ANSI PUMP, 316SS, 2 X 3 - 6 STO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller:  
3600rpm 300GPM @ 150FTH |  
1800rpm 150GPM @ 35FTH |  
SF18103 Standard Bore Cartridge  
Seal C/SC/V/316SS

316SS PUMPS HAVE AN 316SS  
CASING AND STUFFING BOX  
COVER; A 316SS IMPELLER AND  
SLEEVE; AND A 4140 SHAFT.



---

**SKU:** 2196STO, 2X3-6-316SS-  
SF18103

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Summit 2196 Ansi  
Pumps](#)

## PRODUCT DESCRIPTION

www.pfcstore.com - 763-425-7890 / 800-328-2350

## Summit 2196 Pump, Features

- Rear Pull-Out Design
- Efficient Interchangeable Parts
  - Capacities to 6000 GPM
  - Heads to 730 feet
- Temperatures to 700 deg F
  - Fully Open Impeller
- Extra Large Oil Sump
  - Rigid Frame Foot

## Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

## Typical lead time 2 to 4 weeks

[3600RPM Curve](#)

[1800RPM Curve](#)

[Summit Brochure](#)

[Summit Manual](#)

## ADDITIONAL INFORMATION

|                              |  |
|------------------------------|--|
| <b>Weight</b>                | 110 lbs  |
| <b>Dimensions</b>            | 24 × 14 × 18 in  |
| <b>Best Efficiency Point</b> | <a href="#"><u>150 GPM @ 35 FTH, 300 GPM @ 170 FTH</u></a> |
| <b>Wetted Material</b>       | <a href="#"><u>316SS-VITON</u></a>                         |

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

Best Efficiency Point Full Impeller: 3600rpm 300GPM @ 150FTH | 1800rpm  
150GPM @ 35FTH | SF18103 Standard Bore Cartridge Seal C/SC/V/316SS

316SS PUMPS HAVE AN 316SS CASING AND STUFFING BOX COVER; A 316SS  
IMPELLER AND SLEEVE; AND A 4140 SHAFT.