

www.pfcestore.com - 763-425-7890 / 800-328-2350



## SUMMIT 2196 ANSI PUMP, 316SS, 2 X 3 - 8 MTO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller:  
3600rpm 275GPM @ 275FTH |  
1800rpm 150GPM @ 65FTH |  
SF18105 Standard Bore Cartridge  
Seal C/SC/V/316SS

316SS PUMPS HAVE A 316SS  
CASING, STUFFING BOX COVER,  
IMPELLER, AND SLEEVE; AND A  
4140 SHAFT.



---

**SKU:** 2196MTO, 2X3-8-316SS-  
SF18105

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Summit 2196 Ansi  
Pumps](#)

## PRODUCT DESCRIPTION

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

## Summit 2196 Pump, Features

- Rear Pull-Out Design
- Efficient Interchangeable Parts
  - Capacities to 6000 GPM
  - Heads to 730 feet
- Temperatures to 700 deg F
  - Fully Open Impeller
- Extra Large Oil Sump
  - Rigid Frame Foot

## Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

## Typical lead time 2 to 4 weeks

[3600RPM Curve](#)

[1800RPM Curve](#)

[Summit Brochure](#)

[Summit Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	240 lbs
<b>Dimensions</b>	31 × 18 × 18 in
<b>Best Efficiency Point</b>	<a href="#"><u>150 GPM @ 55 FTH, 300 GPM @ 272 FTH</u></a>
<b>Wetted Material</b>	<a href="#"><u>316SS-VITON</u></a>