# PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



## SUMMIT 2196 ANSI PUMP, 316SS, 3 X 4 - 13 MTO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller: 1800rpm 700GPM @ 170FTH | 1200rpm 500GPM @ 65FTH | SF18105 Standard Bore Cartridge Seal C/SC/V/316SS

316SS PUMPS HAVE A 316SS CASING, STUFFING BOX COVER, IMPELLER, AND SLEEVE; AND A 4140 SHAFT.



**SKU:** 2196MTO, 3X4-13-316SS-

SF18105

Stock: Out of stock contact us for

lead time

Categories: Summit 2196 Ansi

<u>Pumps</u>

#### PRODUCT DESCRIPTION



www.pfcestore.com - 763-425-7890 / 800-328-2350

#### **Summit 2196 Pump, Features**

- Rear Pull-Out Design
- Efficient Interchangeable Parts
  - Capacities to 6000 GPM
    - Heads to 730 feet
  - Temperatures to 700 deg F
    - Fully Open Impeller
    - Extra Large Oil Sump
      - Rigid Frame Foot

### **Applications**

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

#### Typical lead time 2 to 4 weeks

1800RPM Curve

1200RPM Curve

Summit Brochure

Summit Manual

#### **ADDITIONAL INFORMATION**

Weight 330 lbs

**Dimensions**  $31 \times 18 \times 18$  in

Best Efficiency Point 500 GPM @ 65 FTH, 700 GPM @ 155 FTH

Wetted Material 316SS-VITON