PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

SUMMIT 2196 ANSI PUMP, 316SS, 3 X 4 - 7 MTO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller: 3600rpm 400GPM @ 200FTH | 1800rpm 200GPM @ 45FTH | SF18105 Standard Bore Cartridge Seal C/SC/V/316SS

316SS PUMPS HAVE A 316SS CASING, STUFFING BOX COVER, IMPELLER, AND SLEEVE; AND A 4140 SHAFT.

SKU: 2196MTO, 3X4-7-316SS-SF18105
Stock: Out of stock contact us for lead time
Categories: Summit 2196 Ansi Pumps

PRODUCT DESCRIPTION

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

Summit 2196 Pump, Features

• Rear Pull-Out Design
• Efficient Interchangeable Parts
• Capacities to 6000 GPM
• Heads to 730 feet
• Temperatures to 700 deg F
• Fully Open Impeller
• Extra Large Oil Sump
• Rigid Frame Foot

Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

Typical lead time 2 to 4 weeks

3600RPM Curve

1800RPM Curve

Summit Brochure

Summit Manual

ADDITIONAL INFORMATION

Weight	240 lbs
Dimensions	31 × 18 × 18 in
Best Efficiency Point	200 GPM @ 45 FTH, 400 GPM @ 200 FTH
Wetted Material	316SS-VITON