


www.pfcstore.com - 763-425-7890 / 800-328-2350



SUMMIT 2196 ANSI PUMP, 316SS, 4 X 6 - 10 MTO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller:
1800rpm 1000GPM @ 90FTH |
1200rpm 600GPM @ 38FTH |
SF18105 Standard Bore Cartridge
Seal C/SC/V/316SS

316SS PUMPS HAVE A 316SS
CASING, STUFFING BOX COVER,
IMPELLER, AND SLEEVE; AND A
4140 SHAFT.



SKU: 2196MTO, 4x6-10-316SS-
SF18105

Stock: Out of stock contact us for
lead time

Categories: [Summit 2196 Ansi
Pumps](#)

PRODUCT DESCRIPTION

www.pfcstore.com - 763-425-7890 / 800-328-2350

Summit 2196 Pump, Features

- Rear Pull-Out Design
- Efficient Interchangeable Parts
 - Capacities to 6000 GPM
 - Heads to 730 feet
 - Temperatures to 700 deg F
 - Fully Open Impeller
 - Extra Large Oil Sump
 - Rigid Frame Foot

Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

Typical lead time 2 to 4 weeks

[1800RPM Curve](#)

[1200RPM Curve](#)

[Summit Brochure](#)

[Summit Manual](#)

ADDITIONAL INFORMATION

Weight	310 lbs
Dimensions	31 × 18 × 18 in
Best Efficiency Point	<u>600 GPM @ 38 FTH, 1000 GPM @ 85 FTH</u>
Wetted Material	<u>316SS-VITON</u>

www.pfcestore.com - 763-425-7890 / 800-328-2350

Best Efficiency Point Full Impeller: 1800rpm 1000GPM @ 90FTH | 1200rpm
600GPM @ 38FTH | SF18105 Standard Bore Cartridge Seal C/SC/V/316SS

316SS PUMPS HAVE A 316SS CASING, STUFFING BOX COVER, IMPELLER, AND
SLEEVE; AND A 4140 SHAFT.