PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



SUMMIT 2196 ANSI PUMP, 316SS, 4 X 6 - 10H MTO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller: 1800rpm 1200GPM @ 80FTH | 1200rpm 800GPM @ 38FTH | SF18105 Standard Bore Cartridge Seal C/SC/V/316SS

316SS PUMPS HAVE A 316SS CASING, STUFFING BOX COVER, IMPELLER, AND SLEEVE; AND A 4140 SHAFT.



SKU: 2196MTO, 4x6-10H-316SS-

SF18105

Stock: Out of stock contact us for

lead time

Categories: Summit 2196 Ansi

<u>Pumps</u>

PRODUCT DESCRIPTION



www.pfcestore.com - 763-425-7890 / 800-328-2350

Summit 2196 Pump, Features

- Rear Pull-Out Design
- Efficient Interchangeable Parts
 - Capacities to 6000 GPM
 - Heads to 730 feet
 - Temperatures to 700 deg F
 - Fully Open Impeller
 - Extra Large Oil Sump
 - Rigid Frame Foot

Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

Typical lead time 2 to 4 weeks

1800RPM Curve

1200RPM Curve

Summit Brochure

Summit Manual

ADDITIONAL INFORMATION

Weight 310 lbs

Dimensions $31 \times 18 \times 18$ in

Best Efficiency Point 800 GPM @ 38 FTH, 1200 GPM @ 80 FTH

Wetted Material 316SS-VITON