

www.pfcstore.com - 763-425-7890 / 800-328-2350



## SUMMIT 2196 ANSI PUMP, CAST IRON/316SS IMPELLER, 1 X 1.5 - 8 STO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller:  
3600rpm 150GPM @ 250FTH |  
1800rpm 80GPM @ 60FTH |  
SF18103 Standard Bore Cartridge  
Seal C/SC/V/316SS

IRON / SS PUMPS HAVE AN IRON  
CASING AND STUFFING BOX  
COVER; A 316SS IMPELLER AND  
SLEEVE; AND A 4140 SHAFT.



**SKU:** 2196STO, 1X1.5-8-SF18103  
**Stock:** Out of stock contact us for  
lead time

**Categories:** [Summit 2196 Ansi  
Pumps](#)

## PRODUCT DESCRIPTION

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

## Summit 2196 Pump, Features

- Rear Pull-Out Design
- Efficient Interchangeable Parts
  - Capacities to 6000 GPM
  - Heads to 730 feet
- Temperatures to 700 deg F
  - Fully Open Impeller
- Extra Large Oil Sump
  - Rigid Frame Foot

## Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

## Typical lead time 2 to 4 weeks

[3600RPM Curve](#)

[1800RPM Curve](#)

[Summit Brochure](#)

[Summit Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	110 lbs
<b>Dimensions</b>	24 × 14 × 18 in
<b>Best Efficiency Point</b>	<a href="#"><u>80 GPM @ 55 FTH, 150 GPM @ 250 FTH</u></a>
<b>Wetted Material</b>	<a href="#"><u>CAST IRON-VITON</u></a>