

www.pfcstore.com - 763-425-7890 / 800-328-2350



SUMMIT 2196 ANSI PUMP, CAST IRON/316SS IMPELLER, 1 X 2 - 10 MTO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller:
3600rpm 160GPM @ 450FTH |
1800rpm 80GPM @ 105FTH |
SF18105 Standard Bore Cartridge
Seal C/SC/V/316SS

IRON / SS PUMPS HAVE AN IRON
CASING AND STUFFING BOX
COVER; A 316SS IMPELLER AND
SLEEVE; AND A 4140 SHAFT.



SKU: 2196MTO, 1x2-10-SF18105
Stock: Out of stock contact us for
lead time

Categories: [Summit 2196 Ansi
Pumps](#)

PRODUCT DESCRIPTION

www.pfcestore.com - 763-425-7890 / 800-328-2350

Summit 2196 Pump, Features

- Rear Pull-Out Design
- Efficient Interchangeable Parts
 - Capacities to 6000 GPM
 - Heads to 730 feet
- Temperatures to 700 deg F
 - Fully Open Impeller
- Extra Large Oil Sump
 - Rigid Frame Foot

Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

Typical lead time 2 to 4 weeks

[3600RPM Curve](#)

[1800RPM Curve](#)

[Summit Brochure](#)

[Summit Manual](#)

ADDITIONAL INFORMATION

Weight	240 lbs
Dimensions	31 × 18 × 18 in
Best Efficiency Point	<u>80 GPM @ 100 FTH, 165 GPM @ 450 FTH</u>
Wetted Material	<u>CAST IRON-VITON</u>