PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



SUMMIT 2196 ANSI PUMP, CAST IRON/316SS IMPELLER, 2 X 3 - 13 MTO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller: 1800rpm 400GPM @ 135FTH | SF18105 Standard Bore Cartridge Seal C/SC/V/316SS

IRON / SS PUMPS HAVE AN IRON CASING AND STUFFING BOX COVER; A 316SS IMPELLER AND SLEEVE; AND A 4140 SHAFT.



SKU: 2196MTO, 2X3-13-SF18105 **Stock:** Out of stock contact us for

lead time

Categories: Summit 2196 Ansi

<u>Pumps</u>

PRODUCT DESCRIPTION



www.pfcestore.com - 763-425-7890 / 800-328-2350

Summit 2196 Pump, Features

- Rear Pull-Out Design
- Efficient Interchangeable Parts
 - Capacities to 6000 GPM
 - Heads to 730 feet
 - Temperatures to 700 deg F
 - Fully Open Impeller
 - Extra Large Oil Sump
 - Rigid Frame Foot

Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

Typical lead time 2 to 4 weeks

1800RPM Curve

Summit Brochure

Summit Manual

ADDITIONAL INFORMATION

Weight 255 lbs

Dimensions $31 \times 18 \times 18$ in

Best Efficiency Point 400 GPM @ 130 FTH

Wetted Material CAST IRON-VITON