PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

SUMMIT 2196 ANSI PUMP, CAST IRON/316SS IMPELLER, 2 X 3 - 6 STO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller: 3600rpm 300GPM @ 150FTH | 1800rpm 150GPM @ 35FTH | SF18103 Standard Bore Cartridge Seal C/SC/V/316SS

IRON / SS PUMPS HAVE AN IRON CASING AND STUFFING BOX COVER; A 316SS IMPELLER AND SLEEVE; AND A 4140 SHAFT.

SKU: 2196STO, 2X3-6-SF18103
Stock: Out of stock contact us for lead time
Categories: Summit 2196 Ansi Pumps

PRODUCT DESCRIPTION

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

Summit 2196 Pump, Features

• Rear Pull-Out Design
• Efficient Interchangeable Parts
• Capacities to 6000 GPM
• Heads to 730 feet
• Temperatures to 700 deg F
• Fully Open Impeller
• Extra Large Oil Sump
• Rigid Frame Foot

Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

Typical lead time 2 to 4 weeks

3600RPM Curve

1800RPM Curve

Summit Brochure

Summit Manual

ADDITIONAL INFORMATION

Weight	110 lbs
Dimensions	24 × 14 × 18 in
Best Efficiency Point	150 GPM @ 35 FTH, 300 GPM @ 170 FTH
Wetted Material	CAST IRON-VITON