PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

# SUMMIT 2196 ANSI PUMP, CAST IRON/316SS IMPELLER, 3 X 4 - 13 MTO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller:
1800rpm 700GPM @ 170FTH |
1200rpm 500GPM @ 65FTH |
SF18105 Standard Bore Cartridge Seal C/SC/V/316SS

IRON / SS PUMPS HAVE AN IRON CASING AND STUFFING BOX COVER; A 316SS IMPELLER AND SLEEVE; AND A 4140 SHAFT.

**SKU:** 2196MTO, 3X4-13-SF18105
**Stock:** Out of stock contact us for lead time
**Categories:** Summit 2196 Ansi Pumps

## PRODUCT DESCRIPTION

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

# Summit 2196 Pump, Features

• Rear Pull-Out Design
• Efficient Interchangeable Parts
• Capacities to 6000 GPM
• Heads to 730 feet
• Temperatures to 700 deg F
• Fully Open Impeller
• Extra Large Oil Sump
• Rigid Frame Foot

## Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

**Typical lead time 2 to 4 weeks**

1800RPM Curve

1200RPM Curve

Summit Brochure

Summit Manual

## ADDITIONAL INFORMATION

| | |
|---|---|
| **Weight** | 330 lbs |
| **Dimensions** | 31 × 18 × 18 in |
| **Best Efficiency Point** | 500 GPM @ 65 FTH, 700 GPM @ 155 FTH |
| **Wetted Material** | CAST IRON-VITON |