

www.pfcstore.com - 763-425-7890 / 800-328-2350



## SUMMIT 2196 ANSI PUMP, CAST IRON/316SS IMPELLER, 3 X 4 - 7 MTO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller:  
3600rpm 400GPM @ 200FTH |  
1800rpm 200GPM @ 45FTH |  
SF18105 Standard Bore Cartridge  
Seal C/SC/V/316SS

IRON / SS PUMPS HAVE AN IRON  
CASING AND STUFFING BOX  
COVER; A 316SS IMPELLER AND  
SLEEVE; AND A 4140 SHAFT.



---

**SKU:** 2196MTO, 3X4-7-SF18105  
**Stock:** Out of stock contact us for  
lead time

**Categories:** [Summit 2196 Ansi  
Pumps](#)

## PRODUCT DESCRIPTION

www.pfcstore.com - 763-425-7890 / 800-328-2350

## Summit 2196 Pump, Features

- Rear Pull-Out Design
- Efficient Interchangeable Parts
  - Capacities to 6000 GPM
  - Heads to 730 feet
- Temperatures to 700 deg F
  - Fully Open Impeller
- Extra Large Oil Sump
  - Rigid Frame Foot

## Applications

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

## Typical lead time 2 to 4 weeks

[3600RPM Curve](#)

[1800RPM Curve](#)

[Summit Brochure](#)

[Summit Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	240 lbs
<b>Dimensions</b>	31 × 18 × 18 in
<b>Best Efficiency Point</b>	<a href="#"><u>200 GPM @ 45 FTH, 400 GPM @ 200 FTH</u></a>
<b>Wetted Material</b>	<a href="#"><u>CAST IRON-VITON</u></a>

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

Best Efficiency Point Full Impeller: 3600rpm 400GPM @ 200FTH | 1800rpm  
200GPM @ 45FTH | SF18105 Standard Bore Cartridge Seal C/SC/V/316SS

IRON / SS PUMPS HAVE AN IRON CASING AND STUFFING BOX COVER; A 316SS  
IMPELLER AND SLEEVE; AND A 4140 SHAFT.