# PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



# SUMMIT 2196 ANSI PUMP, CAST IRON/316SS IMPELLER, 4 X 6 - 10 MTO, WITH VITON CARTRIDGE SEAL

Best Efficiency Point Full Impeller: 1800rpm 1000GPM @ 90FTH | 1200rpm 600GPM @ 38FTH | SF18105 Standard Bore Cartridge Seal C/SC/V/316SS

IRON / SS PUMPS HAVE AN IRON CASING AND STUFFING BOX COVER; A 316SS IMPELLER AND SLEEVE; AND A 4140 SHAFT.



**SKU:** 2196MTO, 4x6-10-SF18105 **Stock:** Out of stock contact us for

lead time

Categories: Summit 2196 Ansi

<u>Pumps</u>

#### PRODUCT DESCRIPTION



www.pfcestore.com - 763-425-7890 / 800-328-2350

## Summit 2196 Pump, Features

- Rear Pull-Out Design
- Efficient Interchangeable Parts
  - Capacities to 6000 GPM
    - Heads to 730 feet
  - Temperatures to 700 deg F
    - Fully Open Impeller
    - Extra Large Oil Sump
      - Rigid Frame Foot

### **Applications**

Water, Chemical, Oil, Pulp, and Paper, General Purpose Pump

# Typical lead time 2 to 4 weeks

1800RPM Curve

1200RPM Curve

Summit Brochure

**Summit Manual** 

#### **ADDITIONAL INFORMATION**

Weight 310 lbs

**Dimensions**  $31 \times 18 \times 18$  in

Best Efficiency Point 600 GPM @ 38 FTH, 1000 GPM @ 85 FTH

Wetted Material CAST IRON-VITON