

www.pfcestore.com - 763-425-7890 / 800-328-2350



SUMMIT CLOSE COUPLED PUMP IN 316SS, 3 PHASE, 15HP, 3600RPM MOTOR

Best Efficiency Point 120 GPM @
250 FTH, NPT 1X2-8A

Mech Seal Car/Silcar/FKM

Baldor Motor 208/230/480 Volts,
TEFC Premium Efficient



SKU: CC-LEK-16-316SS / CC-
AK-13-316SS-8-EJMM3713T

Stock: Out of stock contact us for
lead time

Categories: [Summit Close
Coupled Pumps](#)

Part Number CC1-1X2-8A

PRODUCT DESCRIPTION

Summit CC pumps are horizontal, end suction, centrifugal pumps designed for general service such as clean water, solvents, light oils, non-corrosive

www.pfcstore.com - 763-425-7890 / 800-328-2350

chemicals,
coolants and brines. Available in capacities to 2300 GPM heads to 440 feet, these pumps are an economical and dependable solution for your pumping needs. All Flanges are 125lb ANSI B16.1 rating; NPT connections are standard on 6" and most 8" sizes. A renewable bronze shaft sleeve is standard on cast iron pumps and a 316ss,shaft sleeve is standard on alloy pumps.

Typical Lead time is 2 to 4 weeks

[Curve](#)

[Brochure](#)

[Manual](#)

[Material of Construction](#)

ADDITIONAL INFORMATION

Weight	365 lbs
Dimensions	40 × 20 × 20 in
Best Efficiency Point	120 GPM @ 250 FTH
Phase	3
Wetted Material	316SS-VITON