

www.pfcestore.com - 763-425-7890 / 800-328-2350



# **SUMMIT CLOSE COUPLED PUMP IN 316SS, 3 PHASE, 5HP, 3600RPM MOTOR**

Best Efficiency Point 100 GPM @ 100 FTH. NPT 1X2-5.375

Mech Seal Car/Silcar/FKM

Baldor Motor 208/230/480 Volts, TEFC Premium Efficient



**SKU:** CC-LEK-10-316SS / CC-AK-10-316SS-5.375-EJMM3613T **Stock:** Out of stock contact us for

lead time

Categories: Summit Close
Coupled Pumps

Part Number CC1-1X2-6

### PRODUCT DESCRIPTION

Summit CC pumps are horizontal, end suction, centrifugal pumps designed for general service such as clean water, solvents, light oils, non-corrosive



#### www.pfcestore.com - 763-425-7890 / 800-328-2350

chemicals,

coolants and brines. Available in capacities to 2300 GPM heads to 440 feet, these pumps are an economical and dependable solution for your pumping needs. All Flanges are 125lb ANSI B16.1 rating; NPT connections are standard on 6" and most 8" sizes. A renewable bronze shaft sleeve is standard on cast iron pumps and a 316ss, shaft sleeve is standard on alloy pumps.

## Typical Lead time is 2 to 4 weeks

Curve

Brochure

Manual

**Material of Construction** 

# **ADDITIONAL INFORMATION**

Weight 175 lbs

**Dimensions**  $30 \times 18 \times 16 \text{ in}$ 

**Best Efficiency Point** 100 GPM @ 109 FTH

Phase 3

Wetted Material 316SS-VITON