PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

SUMMIT CLOSE COUPLED PUMP IN 316SS, 3 PHASE, 7.5HP, 3600RPM MOTOR

Best Efficiency Point 140 GPM @ 125 FTH, NPT 1.5X2-6

Mech Seal Car/Silcar/FKM

Baldor Motor 230/480 Volts, TEFC Premium Efficient

SKU: CC-LEK-12-316SS / CC-AK-11-316SS-6-EJMM3709T
Stock: Out of stock contact us for lead time
Categories: Summit Close Coupled Pumps

Part Number CC1.5X2-6J

PRODUCT DESCRIPTION

Summit CC pumps are horizontal, end suction, centrifugal pumps designed for general service such as clean water, solvents, light oils, non-corrosive

chemicals,
coolants and brines. Available in capacities to 2300 GPM heads to 440 feet, these pumps are an economical and dependable solution for your pumping needs. All Flanges are 125lb ANSI B16.1 rating; NPT connections are standard on 6” and most 8” sizes. A renewable bronze shaft sleeve is standard on cast iron pumps and a 316ss,shaft sleeve is standard on alloy pumps.

Typical Lead time is 2 to 4 weeks

Curve

Brochure

Manual

Material of Construction

ADDITIONAL INFORMATION

Weight	235 lbs
Dimensions	30 × 18 × 16 in
Best Efficiency Point	140 GPM @ 125 FTH
Phase	3
Wetted Material	316SS-VITON