

www.pfcestore.com - 763-425-7890 / 800-328-2350



SUMMIT CLOSE COUPLED PUMP IN CAST IRON BRONZE IMPELLER, 3 PHASE, 15HP, 3600RPM MOTOR

Best Efficiency Point 120 GPM @ 250 FTH, NPT 1X2-8A"

Mech Seal Car/Silcar/FKM

Baldor Motor 208/230/480 Volts, TEFC Premium Efficient



 SKU: CC-LEK-16 / CC-AK-13-8-EJMM3713T
Stock: Out of stock contact us for lead time
Categories: <u>Summit Close</u> <u>Coupled Pumps</u>

Part Number CC1-1X2-8A

PRODUCT DESCRIPTION

Page: 1

PFC eStore Pumps, Filters & Controls store with B2B solution



www.pfcestore.com - 763-425-7890 / 800-328-2350

Summit CC pumps are horizontal, end suction, centrifugal pumps designed for general service such as clean water, solvents, light oils, non-corrosive chemicals,

coolants and brines. Available in capacities to 2300 GPM heads to 440 feet, these pumps are an economical and dependable solution for your pumping needs. All Flanges are 125lb ANSI B16.1 rating; NPT connections are standard on 6" and most 8" sizes. A renewable bronze shaft sleeve is standard on cast iron pumps and a 316ss,shaft sleeve is standard on alloy pumps.

Typical Lead time is 2 to 4 weeks

<u>Curve</u>

Brochure

<u>Manual</u>

Material of Construction

ADDITIONAL INFORMATION

Weight	365 lbs
Dimensions	40 × 20 × 20 in
Best Efficiency Point	<u>120 GPM @ 250 FTH</u>
Phase	<u>3</u>
Wetted Material	CAST IRON BRONZE FITTED-VITON