

www.pfcestore.com - 763-425-7890 / 800-328-2350



PUMP IN CAST IRON BRONZE IMPELLER, 3 PHASE, 5HP, 3600RPM MOTOR

Best Efficiency Point 100 GPM @ 100 FTH, NPT 1X2-5.375

Mech Seal Car/Silcar/FKM

Baldor Motor 208/230/480 Volts, TEFC Premium Efficient



SKU: CC-LEK-10 / CC-AK-10-5.375-

EJMM3613T

Stock: Out of stock contact us for

lead time

Categories: Summit Close

Coupled Pumps

Part Number CC1-1X2-6

PRODUCT DESCRIPTION



www.pfcestore.com - 763-425-7890 / 800-328-2350

Summit CC pumps are horizontal, end suction, centrifugal pumps designed for general service such as clean water, solvents, light oils, non-corrosive chemicals,

coolants and brines. Available in capacities to 2300 GPM heads to 440 feet, these pumps are an economical and dependable solution for your pumping needs. All Flanges are 125lb ANSI B16.1 rating; NPT connections are standard on 6" and most 8" sizes. A renewable bronze shaft sleeve is standard on cast iron pumps and a 316ss, shaft sleeve is standard on alloy pumps.

Typical Lead time is 2 to 4 weeks

<u>Curve</u>

Brochure

Manual

Material of Construction

ADDITIONAL INFORMATION

Weight 175 lbs

Dimensions $30 \times 18 \times 16 \text{ in}$

Best Efficiency Point 100 GPM @ 109 FTH

Phase <u>3</u>

Wetted Material CAST IRON BRONZE FITTED-VITON