

www.pfcstore.com - 763-425-7890 / 800-328-2350

SNS



SUMMIT SNS SELF-PRIMING NON-CLOG BARE PUMP, 316SS, MECH SEAL TC/TC/VITON, 3" FLANGE

Best Efficiency Point 1800 RPM, 350 GPM @ 60 FTH. Max RPM 2150

Impeller 2 Vane, Trim 8.75. Max Solids-Spherical Diameter 2.50"

Drop in replacement for the Summit SN series and Gorman Rupp Super T Series Pumps



SKU: SN03SA-PUMP-316SS-8.75
Stock: Out of stock contact us for lead time

Categories: [Summit SNS Pumps](#)

Part Number SN03SA-PUMP-316SS

PRODUCT DESCRIPTION

www.pfcstore.com - 763-425-7890 / 800-328-2350

Features

- Self-Priming Non-Clogging
 - Capacities to 3,400 GPM
- Hard Faced Mechanical Seals Standard
 - Standard Spool Piece Flanges
 - Direct Drive or V-Belt
 - Designed for Easy Maintenance
- Compact Removable Rotating Assembly

Applications

Sump or Bilge Pump, Mild Corrosives, Sewage, Pulp & Paper, Wineries, Fibrous Materials

Typical Lead time 2 to 4 weeks

[SNS Curve](#)

[SNS Dims](#)

[SNS Brochure](#)

[SN Brochure](#)

[SNS Manual](#)

ADDITIONAL INFORMATION

Weight	432 lbs
Dimensions	38 × 24 × 38 in
Best Efficiency Point	<u>350 GPM @ 60 FTH</u>
Wetted Material	<u>316SS-VITON</u>

www.pfcestore.com - 763-425-7890 / 800-328-2350

Best Efficiency Point 1800 RPM, 350 GPM @ 60 FTH. Max RPM 2150

Impeller 2 Vane, Trim 8.75. Max Solids-Spherical Diameter 2.50"

Drop in replacement for the Summit SN series and Gorman Rupp Super T Series Pumps