PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



SUMMIT SNS SELF-PRIMING NON-CLOG BARE PUMP, 316SS, MECH SEAL TC/TC/VITON, 3" FLANGE

Best Efficiency Point 1800 RPM, 350 GPM @ 60 FTH. Max RPM 2150

Impeller 2 Vane, Trim 8.75. Max Solids-Spherical Diameter 2.50"

Drop in replacement for the Summit SN series and Gorman Rupp Super T Series Pumps



SKU: SN03SA-PUMP-316SS-8.75 **Stock:** Out of stock contact us for

lead time

Categories: Summit SNS Pumps

Part Number SN03SA-PUMP-316SS

PRODUCT DESCRIPTION



www.pfcestore.com - 763-425-7890 / 800-328-2350

Features

- Self-Priming Non-Clogging
- Capacities to 3,400 GPM
- Hard Faced Mechanical Seals Standard
 - Standard Spool Piece Flanges
 - Direct Drive or V-Belt
 - Designed for Easy Maintenance
- Compact Removable Rotating Assembly

Applications

Sump or Bilge Pump, Mild Corrosives, Sewage, Pulp & Paper, Wineries, Fibrous Materials

Typical Lead time 2 to 4 weeks

SNS Curve

SNS Dims

SNS Brochure

SN Brochure

SNS Manual

ADDITIONAL INFORMATION

Weight 432 lbs

Dimensions $38 \times 24 \times 38 \text{ in}$

Best Efficiency Point 350 GPM @ 60 FTH

Wetted Material 316SS-VITON



www.pfcestore.com - 763-425-7890 / 800-328-2350