

www.pfcstore.com - 763-425-7890 / 800-328-2350

# SNS



## SUMMIT SNS SELF-PRIMING NON-CLOG BARE PUMP, 316SS, MECH SEAL TC/TC/VITON, 6" FLANGE

Best Efficiency Point 1550 RPM,  
1100 GPM @ 78 FTH. Max RPM  
1750 at Impeller Trim 11.50

Impeller 2 Vane, Trim 12.375. Max  
Solids-Spherical Diameter 3"

Drop in replacement for the  
Summit SN series and Gorman  
Rupp Super T Series Pumps



**SKU:** SN06SA-PUMP-316SS-12.375

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Summit SNS Pumps](#)

**Part Number** SN06SA-  
PUMP-316SS

## PRODUCT DESCRIPTION

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

## Features

- Self-Priming Non-Clogging
- Capacities to 3,400 GPM
- Hard Faced Mechanical Seals Standard
- Standard Spool Piece Flanges
- Direct Drive or V-Belt
- Designed for Easy Maintenance
- Compact Removable Rotating Assembly

## Applications

Sump or Bilge Pump, Mild Corrosives, Sewage, Pulp & Paper, Wineries, Fibrous Materials

**Typical Lead time 2 to 4 weeks**

[SNS Curve](#)

[SNS Dims](#)

[SNS Brochure](#)

[SN Brochure](#)

[SNS Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	890 lbs
<b>Dimensions</b>	62 × 28 × 42 in
<b>Best Efficiency Point</b>	<a href="#"><u>1100 GPM @ 78 FTH</u></a>
<b>Wetted Material</b>	<a href="#"><u>316SS-VITON</u></a>

**www.pfcestore.com - 763-425-7890 / 800-328-2350**