

www.pfcestore.com - 763-425-7890 / 800-328-2350



SUMMIT SNS SELF-PRIMING NON-CLOG BARE PUMP, CAST IRON, MECH SEAL TC/TC/VITON, 6" FLANGE

Best Efficiency Point 1550 RPM, 1100 GPM @ 78 FTH. Max RPM 1750 at Impeller Trim 11.50

Impeller 2 Vane, Trim 12.375. Max Solids-Spherical Diameter 3"

Drop in replacement for the Summit SN series and Gorman Rupp Super T Series Pumps



SKU: SN06SA-PUMP-STD-12.375 **Stock:** Out of stock contact us for

lead time

Categories: Summit SNS Pumps

Part Number SN06SA-PUMP-STD

PRODUCT DESCRIPTION



www.pfcestore.com - 763-425-7890 / 800-328-2350

Features

- Self-Priming Non-Clogging
- Capacities to 3,400 GPM
- Hard Faced Mechanical Seals Standard
 - Standard Spool Piece Flanges
 - Direct Drive or V-Belt
 - Designed for Easy Maintenance
- Compact Removable Rotating Assembly

Applications

Sump or Bilge Pump, Mild Corrosives, Sewage, Pulp & Paper, Wineries, Fibrous Materials

Typical Lead time 2 to 4 weeks

SNS Curve

SNS Dims

SNS Brochure

SN Brochure

SNS Manual

ADDITIONAL INFORMATION

Weight 890 lbs

Dimensions $62 \times 28 \times 42 \text{ in}$

Best Efficiency Point 1100 GPM @ 78 FTH

Wetted Material CAST IRON-VITON



www.pfcestore.com - 763-425-7890 / 800-328-2350