

# SNS



## SUMMIT SNS SELF-PRIMING NON-CLOG BARE PUMP, CAST IRON, MECH SEAL TC/TC/VITON, 6" FLANGE

Best Efficiency Point 1550 RPM, 1100 GPM @ 78 FTH. Max RPM 1750 at Impeller Trim 11.50

Impeller 2 Vane, Trim 12.375. Max Solids-Spherical Diameter 3"

Drop in replacement for the Summit SN series and Gorman Rupp Super T Series Pumps



---

**SKU:** SN06SA-PUMP-STD-12.375  
**Stock:** Out of stock contact us for lead time  
**Categories:** [Summit SNS Pumps](#)

**Part Number** SN06SA-PUMP-STD

## PRODUCT DESCRIPTION

www.pfcestore.com - 763-425-7890 / 800-328-2350

## Features

- Self-Priming Non-Clogging
  - Capacities to 3,400 GPM
- Hard Faced Mechanical Seals Standard
  - Standard Spool Piece Flanges
    - Direct Drive or V-Belt
  - Designed for Easy Maintenance
- Compact Removable Rotating Assembly

## Applications

Sump or Bilge Pump, Mild Corrosives, Sewage, Pulp & Paper, Wineries, Fibrous Materials

**Typical Lead time 2 to 4 weeks**

[SNS Curve](#)

[SNS Dims](#)

[SNS Brochure](#)

[SN Brochure](#)

[SNS Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	890 lbs
<b>Dimensions</b>	62 × 28 × 42 in
<b>Best Efficiency Point</b>	<a href="#"><u>1100 GPM @ 78 FTH</u></a>
<b>Wetted Material</b>	<a href="#"><u>CAST IRON-VITON</u></a>

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

Best Efficiency Point 1550 RPM, 1100 GPM @ 78 FTH. Max RPM 1750 at Impeller Trim 11.50

Impeller 2 Vane, Trim 12.375. Max Solids-Spherical Diameter 3"

Drop in replacement for the Summit SN series and Gorman Rupp Super T Series Pumps