

www.pfcstore.com - 763-425-7890 / 800-328-2350

# SNS



## SUMMIT SNS SELF-PRIMING NON-CLOG BARE PUMP, CAST IRON, MECH SEAL TC/TC/VITON, 3" FLANGE

Best Efficiency Point 1800 RPM, 350 GPM @ 60 FTH. Max RPM 2150

Impeller 2 Vane, Trim 8.75. Max Solids-Spherical Diameter 2.50"

Drop in replacement for the Summit SN series and Gorman Rupp Super T Series Pumps



**SKU:** SN03SA-PUMP-STD-8.75  
**Stock:** Out of stock contact us for lead time

**Categories:** [Summit SNS Pumps](#)

**Part Number** SN03SA-PUMP-STD

## PRODUCT DESCRIPTION

www.pfcstore.com - 763-425-7890 / 800-328-2350

## Features

- Self-Priming Non-Clogging
  - Capacities to 3,400 GPM
- Hard Faced Mechanical Seals Standard
  - Standard Spool Piece Flanges
    - Direct Drive or V-Belt
  - Designed for Easy Maintenance
- Compact Removable Rotating Assembly

## Applications

Sump or Bilge Pump, Mild Corrosives, Sewage, Pulp & Paper, Wineries, Fibrous Materials

**Typical Lead time 2 to 4 weeks**

[SNS Curve](#)

[SNS Dims](#)

[SNS Brochure](#)

[SN Brochure](#)

[SNS Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	432 lbs
<b>Dimensions</b>	38 × 24 × 38 in
<b>Best Efficiency Point</b>	<a href="#"><u>350 GPM @ 60 FTH</u></a>
<b>Wetted Material</b>	<a href="#"><u>CAST IRON-VITON</u></a>

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

Best Efficiency Point 1800 RPM, 350 GPM @ 60 FTH. Max RPM 2150

Impeller 2 Vane, Trim 8.75. Max Solids-Spherical Diameter 2.50"

Drop in replacement for the Summit SN series and Gorman Rupp Super T Series Pumps