


www.pfcstore.com - 763-425-7890 / 800-328-2350



WALCHEM CONTACTING CONDUCTIVITY SENSOR W/ATC FOR BOILER

Contacting Conductivity 1.0 cell
constant, 0-30 mS, 20ft cord. Temp
range 32-401°F, Pressure
0-250PSI.

Sensors are compatible with W400-
WMT8-WMD8-WMB8-WM18-WIND



SKU: 190768

Stock: Out of stock contact us for
lead time

Categories: [Walchem Sensors](#)

Part Number 190768

PRODUCT DESCRIPTION

Boiler Contacting Conductivity Sensors

These cell constant 1.0 sensors are designed for boilers with water up to 10,000 $\mu\text{S}/\text{cm}$ and pressures up to 250 PSI, 16.7 atm). These inline sensors are constructed from stainless steel and PEEK.

www.pfcstore.com - 763-425-7890 / 800-328-2350

If on back order the usual lead time is 2 weeks

Brochure

ADDITIONAL INFORMATION

Weight	4 lbs
Dimensions	8 × 4 × 4 in

Contacting Conductivity 1.0 cell constant, 0-30 mS, 20ft cord. Temp range 32-401°F, Pressure 0-250PSI.

Sensors are compatible with W400-WMT8-WMD8-WMB8-WM18-WIND