

www.pfcstore.com - 763-425-7890 / 800-328-2350



## WALCHEM INTUITION-9, WBL9A000PA CONTROLLER FOR BOILERS - FIXED RELAYS

12 Digital Inputs and Ethernet | 8 powered relays with USA pigtails prewired | USA power cord, 15 Amp | Sensor Input module (2 universal inputs) | Boiler sensor with ATC, 250 psi, 1.0 cell constant, 20 ft. cable

WBL9A000PANNNNNN-ANNNNN



**SKU:** WBL9A000PANNNNNN-

**Stock:** 5 in stock (can be backordered)

**Categories:** [Walchem Controllers](#)

**Part Number**

WBL9A000PANNNNNN-ANNNNN

## PRODUCT DESCRIPTION

The Next Generation of Powerful Control

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

Connect with the Walchem Intuition 9 WBL9 Series controllers and enjoy unparalleled versatility in maintaining your water treatment options.

## KEY BENEFITS:

- Email, alarm messages, datalog, graph, or system summary reports
  - Datalogging
- Ethernet or WiFi for remote access via the Internet, LAN, or optional BACnet or Modbus/TCP
- Large, full-color touchscreen display with icon based programming makes set up easy
- Universal sensor input provides extraordinary flexibility; the same controller can be used with almost any type of sensor needed
  - Four I/O slots allow complete flexibility in adding sensors, analog outputs, and  
Linear Polarization Resistance (LPR) corrosion sensors
    - Multiple language support allows simple setup
- Three to twelve relay control outputs allow the controller to be used in more applications
  - Sixteen virtual inputs and sixteen virtual outputs
  - Economical wall-mount package for easy installation
- On-screen and web page graphing of sensor values and control output status
  - Complete flexibility in the function of each relay

**Estimated delivery is 1 to 3 weeks**

[Brochure](#)

[WCT9 SPECS](#)

[WCT9 Manual](#)

[WCT9 Modbus Manual](#)

www.pfcstore.com - 763-425-7890 / 800-328-2350

## ADDITIONAL INFORMATION

<b>Weight</b>	20 lbs
<b>Dimensions</b>	21 × 20 × 10 in
<b>Controller Type</b>	<u>WBL9A000 Boiler</u>
<b>Relays / Wiring</b>	<u>8 Powered Relays, prewired pigtails</u>

12 Digital Inputs and Ethernet | 8 powered relays with USA pigtails prewired | USA power cord, 15 Amp | Sensor Input module (2 universal inputs) | Boiler sensor with ATC, 250 psi, 1.0 cell constant, 20 ft. cable

WBL9A000PANNNNNN-ANNNNN