

www.pfcstore.com - 763-425-7890 / 800-328-2350



WALCHEM INTUITION-9, WCT9 CONTROLLER FOR COOLING TOWERS - CONFIGURABLE RELAYS

Build your custom Intuition 9.

* If a high pressure manifold is selected, only Hi P sensors and Makeup available.

** Dipper, Pyxis, Chlorine, ClO2, Disinfection, Corrosion sensors NOT available with Submersion mounting.

The builder tool will only show list price, for your discount please Login/Register.

Typical lead-time is 4 weeks.



SKU: WCT9-CONFIGURABLE
RELAYS

Stock: Out of stock contact us for lead time

Categories: [Walchem Controller](#)
[Builder](#)

Model Number WCT9-
CONFIGURABLE RELAYS

PRODUCT DESCRIPTION

The Next Generation of Powerful Control

Connect with the Walchem Intuition 9 WCT9 Series controllers and enjoy unparalleled versatility in maintaining your water treatment options.

KEY BENEFITS:

- Email, alarm messages, datalog, graph, or system summary reports
 - Datalogging
- Ethernet or WiFi for remote access via the Internet, LAN, or optional BACnet or Modbus/TCP
- Large, full-color touchscreen display with icon based programming makes set up easy
- Universal sensor input provides extraordinary flexibility; the same controller can be used with almost any type of sensor needed
 - Four I/O slots allow complete flexibility in adding sensors, analog outputs, and
Linear Polarization Resistance (LPR) corrosion sensors
 - Multiple language support allows simple setup
- Three to twelve relay control outputs allow the controller to be used in more applications
 - Sixteen virtual inputs and sixteen virtual outputs
 - Economical wall-mount package for easy installation
- On-screen and web page graphing of sensor values and control output status
 - Complete flexibility in the function of each relay

Estimated delivery is 4 to 5 weeks

www.pfcstore.com - 763-425-7890 / 800-328-2350

[Brochure](#)

[WCT9 SPECS](#)

[WCT9 Manual](#)

[WCT9 Modbus Manual](#)

ADDITIONAL INFORMATION

Weight	20 lbs
Dimensions	21 × 20 × 10 in

Build your custom Intuition 9.

* If a high pressure manifold is selected, only Hi P sensors and Makeup available.

** Dipper, Pyxis, Chlorine, ClO₂, Disinfection, Corrosion sensors NOT available with Submersion mounting.

The builder tool will only show list price, for your discount please Login/Register.

Typical lead-time is 4 weeks.