

www.pfcstore.com - 763-425-7890 / 800-328-2350



WALCHEM INTUITION WCT6 CONTROLLER FOR COOLING TOWERS

Build your custom Intuition WCT6 controller.

- * If a high pressure manifold is selected, only Hi P sensors and Makeup available.
- ** Dipper, Pyxis, Chlorine, ClO2, Disinfection sensors NOT available with Submersion mounting.
- ^ Requires a sensor board with an analog input
- ~ Requires two analog inputs

The builder tool will only show list price, for your discount please Login/Register.

If you order 6 powered relays with pigtails, Typical lead-time is 1 week.



SKU: WCT6A00P

Stock: N/A

Categories: [Walchem Controller](#)

www.pfcstore.com - 763-425-7890 / 800-328-2350

Builder

Model Number WCT6

Options Selected:

Controller Type:	WCT6 - Cooling tower controller
Relays & Wiring:	A00 - 6 powered relays with USA pigtails prewired +\$171.00
Power Cord:	P - USA power cord +\$28.00
Input Boards #1 (must be in alphabetical order):	C - One combination sensor/analog input board +\$421.00
Input Boards #2 (must be in alphabetical order):	C - One combination sensor/analog input board +\$421.00
Analog Outputs:	N - No Analog Outputs
Ethernet/Communications Protocol:	E - Ethernet board +\$382.00
Sensor Mounting:	P - Flow Switch Manifold on Panel, 3 foot cables, Low Pressure +\$342.00
Sensor #1 (Must be in alphabetical order, with suitable input board selected above, except N last):	A - Graphite contacting conductivity +\$183.00
Sensor #2 (Must be in alphabetical order, with suitable input board selected above, except N last):	F - Flat surface WEL pH, No ATC +\$643.00
Sensor #3 (Must be in alphabetical order, with suitable input board selected above, except N last):	W - Rod Style WEL ORP, 4-20 mA^ +\$926.00

www.pfcestore.com - 763-425-7890 / 800-328-2350

Sensor #4 (Must be in alphabetical order, with suitable input board selected above, except N last):	N - No Sensor
Part Number:	WCT6A00PCCNE-PAFWN

PRODUCT DESCRIPTION

Walchem Intuition 6 cooling tower. Take Control Now and Connect with the Best!

- Large touchscreen display with icon based programming makes setup easy
 - Universal sensor input provides extraordinary flexibility; the same controller can be used with almost any type of sensor needed
 - Six relay control outputs
- Combination sensor input & analog input board that adds even more flexibility
 - Lead/Lag control of relays
- Optional dual analog (4-20 mA) input for Fluorometers or nearly any other process value
 - Multiple language support allows simple setup no matter where your business takes you
 - Economical wall-mount package for easy installation
- On-screen and web page graphing of sensor values and control output status
- The Intuition-6™ with amperometric chlorine sensors can be used for reporting chlorine rural measurements in accordance with EPA Method 334.0
 - Six virtual inputs and six virtual outputs
 - Complete flexibility in the function of each relay
- Email alarm messages, datalogs, graphs, or system summary reports
 - Ethernet option for remote access via the Internet, LAN, BACnet or Modbus/TCP

www.pfcstore.com - 763-425-7890 / 800-328-2350

Estimated delivery is 2 weeks

Contact us for actual lead time

[Walchem WCT6 Brochure](#)

[Walchem WCT6 Manual](#)

ADDITIONAL INFORMATION

Weight	20 lbs
Dimensions	18 × 29 × 10 in

YOU MAY ALSO LIKE...



[**Walchem W100
Controller for
Cooling Towers
& Boilers**](#)