

www.pfcstore.com - 763-425-7890 / 800-328-2350



## WALCHEM INTUITION WCT6 CONTROLLER FOR COOLING TOWERS

**Build your custom Intuition  
WCT6 controller.**

\* If a high pressure manifold is selected, only Hi P sensors and Makeup available.

\*\* Dipper, Pyxis, Chlorine, ClO<sub>2</sub>, Disinfection sensors NOT available with Submersion mounting.

^ Requires a sensor board with an analog input

~ Requires two analog inputs

**The builder tool will only show list price, for your discount please Login/Register.**

**If you order 6 powered relays with pigtails, Typical lead-time is 1 week.**



---

**SKU:** WCT6A00PNNNN-NNNN  
**Stock:** Out of stock contact us for lead time

www.pfcstore.com - 763-425-7890 / 800-328-2350

**Categories:** [Walchem Controller](#)  
[Builder](#)

**Model Number** WCT6

## PRODUCT DESCRIPTION

### **Walchem Intuition 6 cooling tower. Take Control Now and Connect with the Best!**

- Large touchscreen display with icon based programming makes setup easy
  - Universal sensor input provides extraordinary flexibility; the same controller can be used with almost any type of sensor needed
    - Six relay control outputs
  - Combination sensor input & analog input board that adds even more flexibility
    - Lead/Lag control of relays
- Optional dual analog (4-20 mA) input for Fluorometers or nearly any other process value
  - Multiple language support allows simple setup no matter where your business takes you
    - Economical wall-mount package for easy installation
- On-screen and web page graphing of sensor values and control output status
- The Intuition-6™ with amperometric chlorine sensors can be used for reporting chlorine rural measurements in accordance with EPA Method 334.0
  - Six virtual inputs and six virtual outputs
  - Complete flexibility in the function of each relay
- Email alarm messages, datalogs, graphs, or system summary reports
  - Ethernet option for remote access via the Internet, LAN, BACnet or Modbus/TCP

www.pfcestore.com - 763-425-7890 / 800-328-2350

Estimated delivery is 2 weeks

Contact us for actual lead time

[Walchem WCT6 Brochure](#)

[Walchem WCT6 Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	20 lbs
<b>Dimensions</b>	18 × 29 × 10 in

### **Build your custom Intuition WCT6 controller.**

\* If a high pressure manifold is selected, only Hi P sensors and Makeup available.

\*\* Dipper, Pyxis, Chlorine, ClO<sub>2</sub>, Disinfection sensors NOT available with Submersion mounting.

^ Requires a sensor board with an analog input

~ Requires two analog inputs

**The builder tool will only show list price, for your discount please Login/Register.**

**If you order 6 powered relays with pigtails, Typical lead-time is 1 week.**