

www.pfcstore.com - 763-425-7890 / 800-328-2350



WALCHEM IX METERING PUMP

Connections 3/4"NPT | Max GPH
39.6 | Max PSI 145 | Wetted
Material Stainless Steel-PTFE



SKU: IX-D150S6N-TB-U

Stock: Out of stock contact us for
lead time

Categories: [Walchem IX Pumps](#)

Tags: [Walchem IX Pumps](#)

Part Number IX-D150S6N-TB-U

PRODUCT DESCRIPTION

- 1000:1 Turndown Ratio

IX Series pumps use efficient Brushless DC motors for speed control. High resolution motor control adjusts the discharge and suction speeds to meet a full and accurate turndown ratio of 1000:1 and flowrates from 300 L/H down to 7.5mL/H.

- $\pm 1\%$ High Accuracy

Combined with precise motor control, an efficient valve design maintains accurate flow rates to allow a low-cost, mechanically-driven diaphragm pump to achieve a repeatability of $\pm 1\%$.

- 70% Energy Savings

www.pfcestore.com - 763-425-7890 / 800-328-2350

Helical gears and return spring reduce power consumption by up to 70% compared to conventional mechanical diaphragm metering pumps.

- High Compression Pump Head Design

A fixed stroke length and proprietary liquid end design maintains high compression during each stroke, resulting in fast priming and no gas-lock at any flow rate up to full rated pressures.

Estimated Delivery is 2 to 3 weeks

Contact us for actual delivery

Product photo could vary from the actual product

[Walchem Brochure](#)

[Walchem Manual](#)

www.pfcstore.com - 763-425-7890 / 800-328-2350

ADDITIONAL INFORMATION

Weight	38 lbs
Dimensions	14 × 24 × 24 in
Connections	<u>3/4"NPT</u>
Max GPH	<u>39.6</u>
Max PSI	<u>145</u>
Motor Type	<u>Direct Drive</u>
Wetted Material	<u>STAINLESS STEEL-PTFE</u>