PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

WALCHEM PYXIS PTSA SENSOR STAINLESS SENSOR

Measures for PTSA at an expanded range (*0–300ppb*), while simultaneously compensating for Color & Turbidity Interference, to provide a more accurate dosage reading

The ST-500W is a stainless steel inline PTSA Pyxis smart sensor. It is uniquely designed to be directly inserted into the WALCHEM® and alternative fluorometer tee assemblies. **The ST-500W is designed for the WALCHEM® tee system**. Most fluorometers have similar dimensions to this system. This allows drop-in installation into both designs of inline tee assemblies without the need for plumbing modifications.

SKU: ST-500W
Stock: Out of stock contact us for lead time

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

Categories: Walchem Sensors

Model Number ST-500W

GALLERY IMAGES

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

ST-500W INLINE FLUOROMETER

Product Description

The ST-500W is a stainless steel inline PTSA Pyxis smart sensor. It is uniquely designed to be directly inserted into the WALCHEM® and alternative fluorometer tee assemblies. The ST-500W is designed for the WALCHEM® tee system. Most fluorometers have similar dimensions to this system. This allows drop-in installation into both designs of inline tee assemblies without the need for plumbing modifications.

ST-500W Spec Sheet

ADDITIONAL INFORMATION

Measures for PTSA at an expanded range (*0–300ppb*), while simultaneously compensating for Color & Turbidity Interference, to provide a more accurate dosage reading

The ST-500W is a stainless steel inline PTSA Pyxis smart sensor. It is uniquely designed to be directly inserted into the WALCHEM® and alternative fluorometer tee assemblies. **The ST-500W is designed for the WALCHEM® tee system**. Most fluorometers have similar dimensions to this system. This allows drop-in installation into both designs of inline tee assemblies without the need for plumbing modifications.