# PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



# YAMADA AOD PUMP GLOBAL SERIES IN ALUMINUM & HYTREL G15

Aluminum-Hytrel

10 GPM @ 200 FTH / MAX 16.6 GPM

1/2 NPT Female

Max Temp 248°F

Maximum Dry Suction Lift: Rubber fitted pump capability: 13.5' - PTFE fitted pump capability: 11'

Replaces the ARO AODD Pump 660SJ



**SKU:** 854702

**Stock:** Out of stock contact us for

lead time

Categories: Yamada AODD

<u>Pumps</u>

Tags: <u>Yamada Pumps</u> Model Number 854702 Part Number G15AH11



www.pfcestore.com - 763-425-7890 / 800-328-2350

#### PRODUCT DESCRIPTION

#### Yamada AOD Pump

**G15 Global Series** 1/2" AODD pumps provide a maximum flow rate of 16.6 GPM and are available in Aluminum, Stainless Steel (316), Pure Polypropylene and Kynar. We offer a wide selection of diaphragm materials that cover a variety of applications.

### Yamada pumps utilize a Step Spool (S-Spool).

Yamada Global Series pumps do not have an independent pilot valve system (less parts) and consume less air versus the competition. Available with multiport options, these AODD pumps perform extremely well in continuous stop/start operations and provide exceptional suction lift.

## **Estimated delivery 2 weeks**

**Curves & Specs** 

# **ADDITIONAL INFORMATION**

Weight 15 lbs

**Dimensions**  $15 \times 15 \times 16$  in

Connections 1/2"FNPT

Max **GPM** 16.6 **GPM** 

Wetted Material ALUMINUM-HYTREL