PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



YAMADA AOD PUMP GLOBAL SERIES IN PURE POLYPRO HYTREL & BUNA G15

Pure Polypro-Hytrel-Buna

10 GPM @ 100 FTH / MAX 16.6 GPM

1/2 NPT Female

Max Temp 180°F

Maximum Dry Suction Lift: Rubber fitted pump capability: 13.5' - PTFE fitted pump capability: 11'

Replaces the ARO AODD Pump 660SJ



SKU: 854979

Stock: Out of stock contact us for

lead time

Categories: AOD Pumps
Tags: Yamada Pumps
Model Number 854979
Part Number G15PH11



www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

Yamada AOD Pump

G15 Global Series 1/2" AODD pumps provide a maximum flow rate of 16.6 GPM and are available in Aluminum, Stainless Steel (316), Pure Polypropylene and Kynar. We offer a wide selection of diaphragm materials that cover a variety of applications.

Yamada pumps utilize a Step Spool (S-Spool).

Yamada Global Series pumps do not have an independent pilot valve system (less parts) and consume less air versus the competition. Available with multiport options, these AODD pumps perform extremely well in continuous stop/start operations and provide exceptional suction lift.

Estimated delivery 2 weeks

Curves & Specs

ADDITIONAL INFORMATION

Weight 10 lbs

Dimensions $15 \times 15 \times 16$ in

Connections <u>1/2"FNPT</u>

Max **GPM** 16.6 **GPM**

Wetted Material PURE POLYPRO-HYTREL-BUNA