



## YAMADA AOD PUMP NDP-500BSS 316SS & SANTOPRENE W/NPT

Max GPM 226 | 2" FNPT  
connections



**SKU:** 855403

**Stock:** Out of stock contact us for  
lead time

**Categories:** [AOD Pumps](#)

**Tags:** [Yamada Pumps](#)

**Model Number** NDP-500BSS

**Part Number** 855403

## PRODUCT DESCRIPTION

Air Supply Pressure (All Models) 20-125 PSI (1.4-8.7 kgf/cm<sup>2</sup>) Discharge  
Volume Per Cycle Rubber diaphragm: 1.14 gallons. Thermoplastic  
diaphragm: 1.22 gallons. PTFE diaphragm: 0.70 gallons.

Ultimate diaphragm: 0.69 gallons. Maximum Cycles Per Minute\*. Rubber  
diaphragm: 183. Thermoplastic diaphragm: 180. PTFE diaphragm: 259  
Ultimate diaphragm: 302. \*Approximates @ 100 PSI. Maximum Size Solid  
5/16 (8mm). Maximum Dry Suction Lift 18 ft

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

Air Motor. Aluminum air motor standard on metal pumps.. Air Motor Options. Polypropylene (PP) air motor on metal pumps.. PTFE grey coating (XP) on aluminum air motors. Valve Type Ball

**Estimated delivery 2 to 3 weeks**

[Curves & Specs](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	144 lbs
<b>Dimensions</b>	25 × 36 × 25 in
<b>Connections</b>	<a href="#"><u>2" NPT</u></a>
<b>Max GPM</b>	<a href="#"><u>226</u></a>
<b>Wetted Material</b>	<a href="#"><u>316SS &amp; SANTOPRENE</u></a>