



YAMADA AOD PUMP NDP-500BSS 316SS & SANTOPRENE W/NPT

Max GPM 226 | 2" FNPT
connections



SKU: 855403

Stock: Out of stock contact us for
lead time

Categories: [AOD Pumps](#)

Tags: [Yamada Pumps](#)

Model Number NDP-500BSS

Part Number 855403

PRODUCT DESCRIPTION

Air Supply Pressure (All Models) 20-125 PSI (1.4-8.7 kgf/cm²) Discharge
Volume Per Cycle Rubber diaphragm: 1.14 gallons. Thermoplastic
diaphragm: 1.22 gallons. PTFE diaphragm: 0.70 gallons.

Ultimate diaphragm: 0.69 gallons. Maximum Cycles Per Minute*. Rubber
diaphragm: 183. Thermoplastic diaphragm: 180. PTFE diaphragm: 259
Ultimate diaphragm: 302. *Approximates @ 100 PSI. Maximum Size Solid
5/16 (8mm). Maximum Dry Suction Lift 18 ft

www.pfcstore.com - 763-425-7890 / 800-328-2350

Air Motor. Aluminum air motor standard on metal pumps.. Air Motor Options. Polypropylene (PP) air motor on metal pumps.. PTFE grey coating (XP) on aluminum air motors. Valve Type Ball

Estimated delivery 2 to 3 weeks

[Curves & Specs](#)

ADDITIONAL INFORMATION

Weight	144 lbs
Dimensions	25 × 36 × 25 in
Connections	<u>2" NPT</u>
Max GPM	<u>226</u>
Wetted Material	<u>316SS & SANTOPRENE</u>