

www.pfcestore.com - 763-425-7890 / 800-328-2350



YAMADA AOD PUMP NDP-5FST 316SS & PTFE

Max GPM 3.1 | 316SS & PTFE | 1/4 NPT



SKU: 851565 Stock: 15 in stock (can be backordered) Categories: <u>AOD Pumps</u> Tags: <u>Yamada Pumps</u> Model Number NDP-5FST Part Number 851565

PRODUCT DESCRIPTION

3.4 Gallons/Minute Max. 1/4" NPT Fluid Port Intake & Discharge Connection 1/4" Female NPT Air Inlet 1/4" Female NPT (includes ball valve) Air Exhaust 3/8" Female NPT (includes silencer) Air Supply Pressure (All Models) 20 to 100 PSI (1.4 to 7 kgf/cm2) Discharge Volume Per Cycle 0.0085 gallons (35 cc) Maximum Cycles Per Minute All diaphragms: 400 Maximum Dry Suction Lift 5-feet Air Motor Standard: Ryton® Air Motor

PFC eStore

Pumps, Filters & Controls store with B2B



www.pfcestore.com - 763-425-7890 / 800-328-2350

Muffler Internal

MAXIMUM LIQUID TEMPERATURE FITTED WITH PTFE DIAPHRAGM Groundable Acetal 180F (82C) Polypropylene (PPG) 180F (82C) Kynar® (PVDF) 212F (100C) Aluminum (ADC-12) 212F (100C) Stainless Steel (316) 212F (100C)

Estimated delivery 1 to 4 days

Contact us for actual lead time

Product photo could vary from the actual product

Curves & Specs

ADDITIONAL INFORMATION

Weight	7 lbs
Dimensions	$14\times12\times12$ in
Connections	<u>1/4"NPT</u>
Max GPM	<u>3.1</u>
Wetted Material	<u>316SS-PTFE</u>