GOULDS WATER TECHNOLOGY
a xylem brand

02SH08F15T3F2

Technical Data

Company	
Contact	
Tel.	
E-mail	

Operating Data

1	Pump type	Single head pump		Fluid			Water
2	No. of pumps		1	Operating temperature t A		°F	39.2
3	Nominal flow	US g.p.m.	0	pH-value at t A			7
4	Nominal head	ft	0	Density at t A		lb/ft³	62.4
5	Static head	ft	0	Kin. viscosity at t A		ft²/s	1.689E-5
6	Inlet pressure	psi	0	Vapor pressure at t A		psi	14.5
7	Environmental temperature	°F	68	Content of solid%	Solid size	inch	0 0
8	Available system NPSH	ft	0	Altitude		ft	0

Pump Data

9	Design	Highly efficient stainless steel end suction pumps					
10	Execution	Rotation: 12 oClock [STD]		Impeller Ø	Max.	inch	8 1/4
11	Operating speed	rpm	3500		Designed	inch	6 3/16
12	Group		S		Min.	inch	6 3/16
13	Suction		NPS 2.5 / CL150 / ASME B16.5 (e-SH)	Flow	Nominal	US g.p.m.	
14	Discharge port		NPS 2 / CL150 / ASME B16.5 (e-SH)		Max-	US g.p.m.	310
15	Max. casing pressure	psi			Min-	US g.p.m.	70
16	Max. working pressure	psi	67.5	Head	Nominal	ft	
17	Impeller type		Radial impeller		at Qmax	ft	107.3
18	Head H(Q=0)	ft	160		at Qmin	ft	157.3
19	Max. shaft power	hp	13.2	Shaft power		hp	
20	Pump weight	lb	68.0	Efficiency		%	
21	Total weight	lb	On demand	NPSH 3%		ft	

Materials

22	Pump		Shaft Seal	
23	Casing	Stainless steel 316L	John Crane	Elastomer Bellows Shaft Seal
24	Impeller	Stainless steel 316L	Type 21	
25	Wear Ring	Stainless steel 316L	Seal faces	Carbon [STD]
26	Adapter	Gray cast iron class 20B	Stationary ring	Silicon Carbide
27	Ball bearing (outboard)	Steel	Elastomers	FKM
28	Pump shaft	Steel grade 1213	Springs	Stainless steel CF8M (316)
29	Deflector	Buna-N	Other metal parts	Stainless steel CF8M (316)
30	Shaft sleeve	Stainless steel CF8M (316)		
31	Bearing Cover	Gray cast iron class 20B		
32	Ball bearing (inboard)	Steel		
33	Impeller Key	Steel		
34	Seal Housing	Stainless steel 316L		
35	Impeller Washer	Stainless steel CF8M		
36	Bearing Frame	Gray cast iron class 20B		
37	Lip Seal	Not available		
38	V-Ring	Buna-N		
39	Casing bolt with nut (casing to adapter)	Stainless Steel		
40	Retaining ring	Steel		
41				

Motor Data

42	Manufacturer	Baldor			
43	Specific design	NEMA 3 ph TEPE [STD]			
44	Type	Frame 254JM - 15 hp			
45	Rated power	15 hp	Item no.		
46	Nominal speed	3600 rpm	Service factor	1.15	
47	Frame size	254JM	Electric voltage	460 V	
48	Weight lb	257.0			

Base Plate

49	Name		
50	Weight	lb	

Remarks

Project	Project ID	Created by	Created on	Last update
			09-04-19	

GOULDS WATER TECHNOLOGY
a xylem brand

02SH08F15T3F2

Performance Curve

Company
Contact
Tel.
E-mail

	Ø	Delivered Flow Application Range		η	Lift Capability		Shaft Power P2					
		Min.	Max.	Max.	H(Q=0)	η Max.	P2(Q=0)	Max.	η Max.	Frequency	Hz	60
	inch	US g.p.m.	US g.p.m.	US g.p.m.	ft	ft	hp	hp	hp	Operating speed	rpm	3500
										Nominal flow	US g.p.m.	0
Is	6.187	70	310	222	156	135		13.2	11.5	Nominal head	ft	0
Min.	6.187	/	/	222	156	135		/	11.5	Inlet pressure	psi	0
Max.	8.250	/	/	302	275	210		/	20.5	Static head	ft	0

Power datas referced to:

Water [100%] ; 39.2°F; 62.4lb/ft³; 1.69E-5ft²/s



Project	Project ID	Created by	Created on	Last update
			09-04-19	

GOULDS WATER TECHNOLOGY
a xylem brand

02SH08F15T3F2

Dimensions

Company
Contact
Tel.
E-mail

Close coupled
Rotation: 12 oClock [STD]
NEMA 3 ph TEPE [STD]Frame 254JM - 15 hp



Dimensions	[inch]		
A	$11^{1}/_{2}$		
ABmax	$12^{3}/_{8}$		
B	$11^{1}/_{2}$		
Cref	$20^{3}/_{4}$		
D	$6^{1}/_{4}$		
DCmax	6		
DD	$5^{3}/_{4}$		
E	5		
F	5		
G	$^{1}/_{4}$		
H	$^{1}/_{2}$		
L	$12^{1}/_{8}$		
Pmax	$13^{3}/_{8}$		
X	$7^{15}/_{16}$		
Y	4		
Z	$3^{5}/_{8}$		

Connections	
Suction	Discharge port
NPS 2.5	NPS 2
CL150	CL150
ASME B16.5 (e-SH)	ASME B16.5 (e-SH)

Weight	(+/- 5%)
Pump	68 lb
Base Plate	
Motor	257 lb
Total weight	On demand lb

Note: Drawing not to be used for construction purposes. Weights subject to change.

Project	Project ID	Created by	Created on	Last update
			09-04-19	