

Customer	Date	2/1/2019
Contact	Project	
Phone number	Project no.	
Email		

1ST1GDB4

Operating data


Pump type	End Suction Pumps	Fluid	Water
No. of pumps / Reserve	1 / 0	Operating temperature t A	°F 39.2
Nominal flow	US g.p.m. 0	pH-value at t A	7
Nominal head	ft 0	Density at t A	lb/ft³ 62.4
Static head	ft 0	Kin. viscosity at t A	ft²/s 1.69E-5
Inlet pressure	psi 0	Vapor pressure at t A	psi 14.5
Environmental temperature	°F 68	Solids	0
Available system NPSH	ft 0	Altitude	ft 0

Pump data

Make	Goulds Water Technology	Nominal	US g.p.m. ()
Speed	rpm 3500	Flow	Max- US g.p.m. 48.6
Number of stages	1		Min- US g.p.m.
Max. casing pressure	psi		Nominal ft
Max. working pressure	psi 58.8	Head	at Qmax ft 76.2
Head H(Q=0)	ft 140		at Qmin ft 135.6
Weight	lb On demand	Shaft power	hp ()
	Max. inch 6 1/8	Max. shaft power	hp 1.9
Impeller R	designed inch 5 3/4	Efficiency	%
	Min. inch 4 1/16	NPSH 3%	ft

Shaft Seal

Type 21 NPE	John Crane
NPE Mechanical Seal	
1 - Rotating Face	Carbon
2 - Stationary Face	Silicon Carbide
3 - Elastomers	Viton
4 - Metal Components	AlSI 316 SS



Motor data

Manufacturer	Bluffton	Electric voltage	208 V	Speed	3500 rpm	Insulation class	B
Specific design	3ph XP Premium Efficiency			Frame size	56J BB	Colour	RAL 5010
Type	F08C32E6EB1G	Electric current	0 A				
Rated power	2 hp	Degree of protection	IP 55				

Remarks:

Customer	Date 2/1/2019
Contact	Project
Phone number	Project no.
Email	

1ST1GDB4

Pump Materials

100-Casing	AISI 316L SS
101-Impeller	AISI 316L SS
108-Motor adapter	AISI 316L SS
108A-Motor adapter seal vent/flush	AISI 316L SS
123-Deflector	BUNA-N
184-Seal housing	AISI 316L SS
184 A-Seal housing seal vent/flush	AISI 316L SS
347-Guide vane	AISI 316L SS
349-Seal ring, guide vane	Viton
370-Socket head screws, casing	AISI 410 SS
371-Bolts, motor	Plated Steel
408-Drain and vent plug, casing	AISI 316L SS
412B-O-ring, drain and vent plug	Viton
513-O-ring, casing	Viton
Motor-NEMA standard, 56J flange	-

Remarks:

Customer	Date	2/1/2019
Contact	Project	
Phone number	Project no.	
Email		

1ST1GDB4


Hydraulic Data

Operating Data Specification		Hydraulic data (duty point)	Impeller design	
Flow	0 US g.p.m.	Flow	Impeller R	5 ³ / ₄ "
Head	0 ft	Head	Frequency	60 Hz
Static head	0 ft		Speed	3500 rpm

Power data referred to:

Water [100%] ; 39.2°F; 62.4lb/ft³; 1.69E-5ft²/s


Performance according to ISO 9906 - Annex A



Customer	Date	2/1/2019
Contact	Project	
Phone number	Project no.	
Email		

1ST1GDB4

Drawing



Dimensions inch

C. Max	$12\frac{11}{16}$					Weight On demand
Discharge	1					
M	$7\frac{5}{16}$					
Suction	$1\frac{1}{4}$					
W	$3\frac{5}{16}$					
X	$4\frac{3}{8}$					
Y	2					