

|                       |                        |                 |
|-----------------------|------------------------|-----------------|
| PROJECT: _____        | UNIT TAG: _____        | QUANTITY: _____ |
| REPRESENTATIVE: _____ | TYPE OF SERVICE: _____ | DATE: _____     |
| ENGINEER: _____       | SUBMITTED BY: _____    | DATE: _____     |
| CONTRACTOR: _____     | APPROVED BY: _____     | DATE: _____     |
|                       | ORDER NO.: _____       | DATE: _____     |





### CR 5-4A-FGJ-A-E-HQQE

Vertical, multistage centrifugal pump with suction and discharge ports on the same level. The pump head and base are in cast iron. All other wetted parts are in stainless steel (EN 1.4301)(AISI 304)

Product photo could vary from the actual product

| Conditions of Service   | Pump Data                                            | Motor Data                   |
|-------------------------|------------------------------------------------------|------------------------------|
| Flow: _____             | Max pressure at stated temperature: 363 psi / 250 °F | Rated power - P2: 1.5 HP     |
| Head: _____             | Liquid temperature range: -4 .. 248 °F               | Rated voltage: 115/208-230 V |
| Efficiency: _____       | Maximum ambient temperature: 104 °F                  | Main frequency: 60 Hz        |
| Liquid: Water           | Approvals: CURUS, NSF61                              | Insulation class: B          |
| Temperature: 68 °F      | Shaft seal: HQQE                                     | Motor protection: NONE       |
| NPSH required: ft       | Product number: 96084254                             | Motor type: Baldor           |
| Viscosity: _____        |                                                      |                              |
| Specific Gravity: 1.000 |                                                      |                              |





**Materials:**

|                  |                                                 |
|------------------|-------------------------------------------------|
| Base:            | Cast iron<br>EN 1561 EN-GJL-200<br>ASTM A48-25B |
| Impeller:        | Stainless steel<br>AISI 304<br>EN 1.4301        |
| Material code:   | A                                               |
| Code for rubber: | E                                               |

| Count | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1     | <p><b>CR 5-4A-FGJ-A-E-HQQE</b></p>  <p>Product No.: <a href="#">96084254</a><br/>Vertical, non-self-priming, multistage, in-line, centrifugal pump for installation in pipe systems and mounting on a foundation.</p> <p>The pump has the following characteristics:</p> <ul style="list-style-type: none"> <li>- Impellers and intermediate chambers are made of</li> <li>- The shaft seal has assembly length according to EN 12756.</li> <li>- Power transmission is via cast iron split coupling.</li> </ul> <p>The motor is a 1-phase AC motor.</p> <p>Controls:</p> <p>Frequency converter: NONE</p> <p><b>Liquid:</b></p> <p>Pumped liquid: Water<br/>Liquid temperature range: -4 .. 248 °F<br/>Selected liquid temperature: 68 °F<br/>Density: 62.29 lb/ft³</p> <p><b>Technical:</b></p> <p>Rated pump speed: 3450 rpm<br/>Rated flow: 30.4 US gpm<br/>Rated head: 93.51 ft<br/>Pump orientation: Vertical<br/>Shaft seal arrangement: Single<br/>Code for shaft seal: HQQE<br/>Approvals on nameplate: CURUS,NSF61<br/>Curve tolerance: ISO9906:2012 3B</p> <p><b>Materials:</b></p> <p>Base: Cast iron<br/>EN 1561 EN-GJL-200<br/>ASTM A48-25B</p> <p>Impeller: Stainless steel<br/>EN 1.4301<br/>AISI 304</p> <p>Bearing: SIC</p> <p><b>Installation:</b></p> <p>Maximum ambient temperature: 104 °F<br/>Maximum operating pressure: 362.59 psi<br/>Max pressure at stated temperature: 363 psi / 250 °F<br/>363 psi / -4 °F</p> <p>Type of connection: DIN / ANSI / JIS</p> |



Company name:

Created by:


Phone:

Date:




5/10/2019

| Count | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|       | <p>Size of inlet connection: DN 25/32<br/>Size of suction port: 1 1/4 inch<br/>Size of outlet connection: DN 25/32<br/>Size of outlet port: 1 1/4 inch<br/>Pressure rating for pipe connection: PN 25<br/>Flange rating inlet: 250 lb<br/>Flange size for motor: 56C</p> <p><b>Electrical data:</b><br/>Motor standard: NEMA<br/>Motor type: Baldor<br/>Rated power - P2: 1.5 HP<br/>Power (P2) required by pump: 1.5 HP<br/>Main frequency: 60 Hz<br/>Rated voltage: 1 x 115/208-230 V<br/>Service factor: 1.30<br/>Rated current: 17/9,50-8,60 A<br/>Rated speed: 3450 rpm<br/>Number of poles: 2<br/>Insulation class (IEC 85): B<br/>Motor Number: 84Z04007</p> <p><b>Others:</b><br/>Net weight: 85 lb<br/>Gross weight: 96 lb<br/>Shipping volume: 6.11 ft<sup>3</sup><br/>Country of origin: US<br/>Custom tariff no.: 8413.70.2040</p> |

## 96084254 CR 5-4A-FGJ-A-E-HQQE 60 Hz



| Description                           | Value                |
|---------------------------------------|----------------------|
| <b>General information:</b>           |                      |
| Product name:                         | CR 5-4A-FGJ-A-E-HQQE |
| Product No.:                          | 96084254             |
| EAN:                                  | 5700395190922        |
| <b>Technical:</b>                     |                      |
| Rated pump speed:                     | 3450 rpm             |
| Rated flow:                           | 30.4 US gpm          |
| Rated head:                           | 93.51 ft             |
| Head max:                             | 135.5 ft             |
| Stages:                               | 4                    |
| Impellers:                            | 4                    |
| Number of reduced-diameter impellers: | 0                    |
| Low NPSH:                             | N                    |
| Pump orientation:                     | Vertical             |
| Shaft seal arrangement:               | Single               |
| Code for shaft seal:                  | HQQE                 |
| Approvals on nameplate:               | CURUS, NSF61         |
| Curve tolerance:                      | ISO9906:2012 3B      |
| Pump version:                         | A                    |
| Model:                                | A                    |
| Cooling:                              | TEFC                 |
| <b>Materials:</b>                     |                      |
| Base:                                 | Cast iron            |
|                                       | EN 1561 EN-GJL-200   |
|                                       | ASTM A48-25B         |
| Impeller:                             | Stainless steel      |
|                                       | EN 1.4301            |
|                                       | AISI 304             |
| Material code:                        | A                    |
| Code for rubber:                      | E                    |
| Bearing:                              | SIC                  |
| <b>Installation:</b>                  |                      |
| Maximum ambient temperature:          | 104 °F               |
| Maximum operating pressure:           | 362.59 psi           |
| Max pressure at stated temperature:   | 363 psi / 250 °F     |
|                                       | 363 psi / -4 °F      |
| Type of connection:                   | DIN / ANSI / JIS     |
| Size of inlet connection:             | DN 25/32             |
| Size of suction port:                 | 1 1/4 inch           |
| Size of outlet connection:            | DN 25/32             |
| Size of outlet port:                  | 1 1/4 inch           |
| Pressure rating for pipe connection:  | PN 25                |
| Flange rating inlet:                  | 250 lb               |
| Flange size for motor:                | 56C                  |
| Connect code:                         | FGJ                  |
| <b>Liquid:</b>                        |                      |
| Pumped liquid:                        | Water                |
| Liquid temperature range:             | -4 .. 248 °F         |
| Selected liquid temperature:          | 68 °F                |
| Density:                              | 62.29 lb/ft³         |
| <b>Electrical data:</b>               |                      |
| Motor standard:                       | NEMA                 |
| Motor type:                           | Baldor               |
| Rated power - P2:                     | 1.5 HP               |
| Power (P2) required by pump:          | 1.5 HP               |
| Main frequency:                       | 60 Hz                |
| Rated voltage:                        | 1 x 115/208-230 V    |
| Service factor:                       | 1.30                 |





Company name:

Created by:


Phone:

Date:

5/10/2019

| Description                | Value                |
|----------------------------|----------------------|
| Rated current:             | 17/9,50-8,60 A       |
| Load current:              | 20,4/11,3-10,2 A     |
| Rated speed:               | 3450 rpm             |
| Number of poles:           | 2                    |
| Insulation class (IEC 85): | B                    |
| Motor protection:          | NONE                 |
| Motor Number:              | 84Z04007             |
| <b>Controls:</b>           |                      |
| Frequency converter:       | NONE                 |
| <b>Others:</b>             |                      |
| Net weight:                | 85 lb                |
| Gross weight:              | 96 lb                |
| Shipping volume:           | 6.11 ft <sup>3</sup> |
| Country of origin:         | US                   |
| Custom tariff no.:         | 8413.70.2040         |

## 96084254 CR 5-4A-FGJ-A-E-HQQE 60 Hz




Note! All units are in [in] unless otherwise stated.

Disclaimer: This simplified dimensional drawing does not show all details.



**96084254 CR 5-4A-FGJ-A-E-HQQE 60 Hz**



All units are [in] unless otherwise presented.