

PROJECT:	UNIT TAG:	QUANTITY:
REPRESENTATIVE:	TYPE OF SERVICE:	DATE:
ENGINEER:	SUBMITTED BY:	DATE:
CONTRACTOR:	APPROVED BY:	DATE:
	ORDER NO.:	




Product photo could vary from the actual product

CR 45-6-2A-G-A-V-HQQV

Vertical, multistage centrifugal pump with suction and discharge ports on the same level. The pump head and base are in cast iron. All other wetted parts are in stainless steel (EN 1.4301) (AISI 304)

Conditions of Service	Pump Data	Motor Data
Flow: _____	Max pressure at stated temperature: 435 psi / 194 °F	Rated power - P2: 50 HP
Head: _____	Liquid temperature range: -4 .. 194 °F	Rated voltage: 230/460 V
Efficiency: _____	Maximum ambient temperature: 122 °F	Main frequency: 60 Hz
Liquid: Water	Approvals: CURUS	Enclosure class: 54 Dust/Splashing
Temperature: 68 °F	Shaft seal: HQQV	Insulation class: F
NPSH required: ft	Product number: 96419253	Motor protection: NONE
Viscosity: _____		Motor type: Baldor
Specific Gravity: 1.000		





Cast iron

ASTM A536 80-55-06

Stainless steel

EN 1.4301

A

V

Count	Description
1	CR 45-6-2A-G-A-V-HQQV  Product No.: 96419253 Vertical, non-self-priming, multistage, in-line, centrifugal pump for installation in pipe systems and mounting on a foundation. The pump has the following characteristics: - Impellers and intermediate chambers are made of - The shaft seal has assembly length according to EN 12756. - Power transmission is via cast iron split coupling. The motor is a 3-phase AC motor. Controls: Frequency converter: NONE Liquid: Pumped liquid: Water Liquid temperature range: -4 .. 194 °F Selected liquid temperature: 68 °F Density: 62.29 lb/ft³ Technical: Rated pump speed: 3550 rpm Rated flow: 238 US gpm Rated head: 541 ft Pump orientation: Vertical Shaft seal arrangement: Single Code for shaft seal: HQQV Approvals on nameplate: CURUS Curve tolerance: ISO9906:2012 3B Materials: Base: Cast iron EN 1563 EN-GJS-500-7 ASTM A536 80-55-06 Impeller: Stainless steel EN 1.4301 AISI 304 Bearing: SIC Support bearing: Grafflon Installation: Maximum ambient temperature: 122 °F Maximum operating pressure: 435.11 psi Max pressure at stated temperature: 435 psi / 194 °F 435 psi / -4 °F Type of connection: ANSI Size of suction port: 3 inch Size of outlet port: 3 inch Pressure rating for pipe connection: PN 40 Flange rating inlet: 300 lb Flange size for motor: 324TC Electrical data:




Company name:
Created by:
Phone:





Date: 5/13/2019

Count	Description
	Motor standard: NEMA Motor type: Baldor IE Efficiency class: NEMA Premium / IE3 60Hz Rated power - P2: 50 HP Power (P2) required by pump: 50 HP Main frequency: 60 Hz Rated voltage: 3 x 230/460 V Service factor: 1.15 Rated current: 112/56 A Cos phi - power factor: 0.87 Rated speed: 3540 rpm IE efficiency: IE3 93,6% Number of poles: 2 Enclosure class (IEC 34-5): 54 Dust/Splashing Insulation class (IEC 85): F Motor Number: 84Z03650 Others: Net weight: 767 lb Gross weight: 785 lb Shipping volume: 39.9 ft³ Country of origin: US Custom tariff no.: 8413.70.2040

96419253 CR 45-6-2A-G-A-V-HQQV 60 Hz



Description	Value
General information:	
Product name:	CR 45-6-2A-G-A-V-HQQV
Product No.:	96419253
EAN:	5700390752699
Technical:	
Rated pump speed:	3550 rpm
Rated flow:	238 US gpm
Rated head:	541 ft
Head max:	678.5 ft
Stages:	6
Impellers:	6
Number of reduced-diameter impellers:	2
Low NPSH:	N
Pump orientation:	Vertical
Shaft seal arrangement:	Single
Code for shaft seal:	HQQV
Approvals on nameplate:	CURUS
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Model:	B
Cooling:	TEFC
Materials:	
Base:	Cast iron
	EN 1563 EN-GJS-500-7
	ASTM A536 80-55-06
Impeller:	Stainless steel
	EN 1.4301
	AISI 304
Material code:	A
Code for rubber:	V
Bearing:	SIC
Support bearing:	Graflon
Installation:	
Maximum ambient temperature:	122 °F
Maximum operating pressure:	435.11 psi
Max pressure at stated temperature:	435 psi / 194 °F
	435 psi / -4 °F
Type of connection:	ANSI
Size of suction port:	3 inch
Size of outlet port:	3 inch
Pressure rating for pipe connection:	PN 40
Flange rating inlet:	300 lb
Flange size for motor:	324TC
Connect code:	G
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-4 .. 194 °F
Selected liquid temperature:	68 °F
Density:	62.29 lb/ft ³
Electrical data:	
Motor standard:	NEMA
Motor type:	Baldor
IE Efficiency class:	NEMA Premium / IE3 60Hz
Rated power - P2:	50 HP
Power (P2) required by pump:	50 HP
KVA code:	G
Main frequency:	60 Hz
Rated voltage:	3 x 230/460 V
Service factor:	1.15
Rated current:	112/56 A
Load current:	128/64 A
Cos phi - power factor:	0.87
Rated speed:	3540 rpm
IE efficiency:	IE3 93,6%
Number of poles:	2
Enclosure class (IEC 34-5):	54 Dust/Splashing







Company name:
Created by:
Phone:

Date: 5/13/2019

Description	Value
Insulation class (IEC 85):	F
Motor protection:	NONE
Motor Number:	84Z03650
Controls:	
Frequency converter:	NONE
Others:	
Net weight:	767 lb
Gross weight:	785 lb
Shipping volume:	39.9 ft³
Sales region:	Namreg
Country of origin:	US
Custom tariff no.:	8413.70.2040

96419253 CR 45-6-2A-G-A-V-HQQV 60 Hz



96419253 CR 45-6-2A-G-A-V-HQQV 60 Hz

