

Company name: Created by: Phone:

Date: 26/03/2020

Qty. | Description

1 | CM 1-8 A-S-I-E-AQQE E-A-A-N



Note! Product picture may differ from actual product

Product No.: 99080196

Compact, reliable, horizontal, multistage, end-suction centrifugal pump with axial suction port and radial discharge port. Pump materials in contact with the liquid are in stainless steel. The mechanical shaft seal is a special designed, unbalanced O-ring seal. Pipework connection is via internal NPT pipe threads.

The pump is fitted with a 3-phase, foot-mounted, fan-cooled asynchronous motor.

Controls:

Frequency converter: NONE

Liquid:

Pumped liquid: Water
Liquid temperature range: -4 .. 248 °F
Selected liquid temperature: 68 °F
Density: 62.29 lb/ft³

Technical:

Pump speed on which pump data are based: 3480 rpm

Actual calculated flow: 9.02 US GPM
Rated flow: 8.98 US GPM
Resulting head of the pump: 227.2 ft
Rated head: 238.1 ft
Code for shaft seal: AQQE

Curve tolerance: ISO9906:2012 3B

Materials:

Pump housing: Stainless steel

EN 1.4301 AISI 304 Stainless steel

Impeller: Stainless steel

EN 1.4301 AISI 304

Installation:

Range of ambient temperature: -4 .. 131 °F

Maximum operating pressure: 232.06 psi

Max pressure at stated temp: 232 psi / 194 °F

145 psi / 250 °F

Type of connection: NPT(F)
Size of inlet connection: 1 inch
Size of outlet connection: 1 inch
Outlet position: 12

Electrical data:

Motor standard: NEMA Frame size: 80B



Company name: Created by: Phone:

Date: 26/03/2020

Qty. | Description

IE efficiency class: IE3 / NEMA Premium

Rated power - P2: 1.48 HP
Mains frequency: 60 Hz
Suitable for 50/60 Hz: N
Phases: 3

Rated voltage: 208-230YY/440-480Y V

Service factor: 1.00

Rated current: 5,2-5,1/2,55-2,65 A Rated speed: 3430-3470 rpm

Enclosure class (IEC 34-5): IP55
Insulation class (IEC 85): F
Built-in motor protection: NONE

Others:

Terminal box position: 12
Minimum efficiency index, MEI ≥: 0.68
Net weight: 39.4 lb
Gross weight: 44.9 lb

Approvals: CE,WRAS,ACS,TR,EAC,CURUS