

Customer	Date	11.03.2020
Contact	Project	
Phone number	Project no.	
Email		

5SV15GG4F60

Operating data


Pump type	Multi-Stage Pumps	Fluid	Water
No. of pumps / Reserve	1 / 0	Operating temperature t A	°F 39.2
Nominal flow	US g.p.m. 30	pH-value at t A	7
Nominal head	ft 399.9	Density at t A	lb/ft³ 62.4
Static head	ft 0	Kin. viscosity at t A	ft²/s 1.689E-5
Inlet pressure	psi 0	Vapor pressure at t A	psi 14.5
Environmental temperature	°F 68	Solids	0
Available system NPSH	ft 0	Altitude	ft 0

Pump data

Make	Goulds Water Technology	Nominal	US g.p.m. 30.3 (30.3)
Speed	rpm 3500	Max-	US g.p.m. 43.7
No. of stages	15	Min-	US g.p.m.
Max. working pressure	psi 224.1	Nominal	ft 406.8
Head H(Q=0)	ft 520	at Qmax	ft 251.2
Weight	lb 137	at Qmin	ft 516.8
Efficiency	% 70.39	Shaft power	hp 4.3 (4.3)
NPSH 3%	ft 6	Max. shaft power	hp 4.9

Shaft Seal

Single Seal	Xylem
Mechanical Seals	
1 - Rotating Face	Carbon
2 - Stationary Face	Silicon Carbide Graphite Filled
3 - Elastomers	Viton
4 - Spring	316SS
5 - Metal Components	316SS



Motor data

Manufacturer	Baldor	Electric voltage	208 V	Speed	3500 rpm	Insulation class	F
Specific design	3ph TPE			Frame size	184TC	Colour	RAL 5010
Type	208-230/460V 184TC (V10A32E5BD2S)			Degree of protection	TEPE		
Rated power	5 hp	Electric current	12.4 A				


Remarks:

Customer	Date 11.03.2020
Contact	Project
Phone number	Project no.
Email	

5SV15GG4F60

Pump Materials

1 - Pump Body	Cast Iron (ASTM Class 35/40B)
2 - Impeller	Stainless Steel (AISI 304)
3 - Diffuser	Stainless Steel (AISI 304)
4 - Casing	Stainless Steel (AISI 316L)
5 - Shaft	Stainless Steel (AISI 316)
6 - Adapter	Cast Iron (ASTM Class 35/40B)
7 - Base	N/A
8 - Coupling	Aluminum (A384.0-F)
9 - Seal Plate	Stainless Steel (AISI 316L)
10 - Mechanical Seal	Refer Mechanical Seals
11 - Elastomers	Refer Mechanical Seals
12 - Coupling Guard	Stainless Steel (AISI 304)
13 - Shaft Sleeve and Bushing	Tungsten carbide
14 - Fill/Drain Plugs	Stainless Steel (AISI 316)
15 - Tie Rods	Carbon Steel / Zinc Plated (A29 Gr.1045)
16 - Wear Ring	PPS
17 - Seal Gland	Stainless Steel (AISI 316)



Remarks:

Customer	Date	11.03.2020
Contact	Project	
Phone number	Project no.	
Email		

5SV15GG4F60


Hydraulic Data

Operating Data Specification		Hydraulic data (duty point)		Impeller design	
Flow	30 US g.p.m.	Flow	30.3 US g.p.m.	Impeller R	"
Head	400 ft	Head	407 ft	Frequency	60 Hz
Static head	0 ft			Speed	3500 rpm

Power datas referred to:

Water [100%] ; 39.2°F; 62.4lb/ft³; 1.69E-5ft²/s


Performance according to ISO 9906 - Annex A



Customer	Date	11.03.2020
Contact	Project	
Phone number	Project no.	
Email		

5SV15GG4F60

Drawing



Dimensions inch

D1 max	8 1/2					Weight
D2	8 7/8					137 lb
L1	26 3/8					
L2	15 3/16					
L3	26 3/8					
L4	17 3/8					
L6	25 3/8					
M.Ref	6 7/8					
NEMA Frame	184TC					