

|              |             |            |
|--------------|-------------|------------|
| Customer     | Date        | 30.06.2021 |
| Contact      | Project     |            |
| Phone number | Project no. |            |
| Email        |             |            |

## HVL3D3-10SV6GG4F60-G

### Operating data

|                             |                        |                           |         |
|-----------------------------|------------------------|---------------------------|---------|
| Pumpe type                  | Single-/Multi-pump set | Fluid                     | Water   |
| No. of pumps / Standby pump | 3 / 0                  | Operating temperature t A | °F 39.2 |
| Nominal flow                | US g.p.m. 0            |                           |         |
| Nominal head                | ft 0                   |                           |         |
| Static head                 | ft 0                   |                           |         |
| Inlet pressure              | psi 0                  |                           |         |
| Environmental temperature   | °F 68                  |                           |         |
| Available system NPSH       | ft 0                   |                           |         |

### Pump data

|                        |               |                  |           |                |
|------------------------|---------------|------------------|-----------|----------------|
| Make                   | Goulds        | Nominal          | US g.p.m. | ( )            |
| Speed                  | rpm 3500      | Flow             | Max-      | US g.p.m. 74.4 |
| No. of stages          | 1             |                  | Min-      | US g.p.m.      |
| Max. casing pressure   | psi           |                  | Nominal   | ft             |
| Max. working pressure  | psi 142.4     | Head             | at Qmax   | ft 157.5       |
| Head H(Q=0)            | ft 330        |                  | at Qmin   | ft 328.5       |
| Weight                 | lb 872        | Shaft power      | hp        | ( )            |
| Communication Protocol | None Selected | Max. shaft power | hp        | 15.9           |
|                        |               | Efficiency       | %         |                |
|                        |               | NPSH 3%          | ft        |                |

### Pump Materials

|                               |                                           |
|-------------------------------|-------------------------------------------|
| 1 - Pump Body                 | Stainless Steel (AISI 304)                |
| 2 - Impeller                  | Stainless Steel (AISI 304)                |
| 3 - Diffuser                  | Stainless Steel (AISI 304)                |
| 4 - Casing                    | Stainless Steel (AISI 316L)               |
| 5 - Shaft                     | Stainless Steel (AISI 316)                |
| 6 - Adapter                   | Cast Iron (ASTM Class 35/40B)             |
| 7 - Base                      | Aluminum (A384.0-F)                       |
| 8 - Coupling                  | Aluminum (A384.0-F)                       |
| 9 - Seal Plate                | Stainless Steel (AISI 316L)               |
| 10 - Coupling Guard           | Stainless Steel (AISI 304)                |
| 11 - Shaft Sleeve and Bushing | Tungsten carbide                          |
| 12 - Fill/Drain Plugs         | Stainless Steel (AISI 316)                |
| 13 - Tie Rods                 | Carbon Steel / Zinc Plated (A29 Gr. 1045) |
| 14 - Wear Ring                | PPS                                       |
| 15 - Seal Gland               | Stainless Steel (AISI 316)                |

### Shaft Seal

|                      |                                 |
|----------------------|---------------------------------|
| 1 - Rotating Face    | Carbon                          |
| 2 - Stationary Face  | Silicon Carbide Graphite Filled |
| 3 - Elastomers       | Viton                           |
| 4 - Spring           | 316SS                           |
| 5 - Metal Components | 316SS                           |

### Motor data

|                 |                |                      |       |
|-----------------|----------------|----------------------|-------|
| Specific design | 3ph TEPE (eHV) |                      |       |
| Type            | V10A32E5BD2S   | Electric voltage     | 460 V |
| Rated power     | 5 hp           | Electric current     | 0 A   |
| Speed           | 3500 rpm       | Degree of protection | IP 55 |
| Frame size      | 184TC          | Insulation class     | B     |




|              |             |            |
|--------------|-------------|------------|
| Customer     | Date        | 30.06.2021 |
| Contact      | Project     |            |
| Phone number | Project no. |            |
| Email        |             |            |

## HVL3D3-10SV6GG4F60-G

### Hydraulic Data

| Operating Data Specification | Hydraulic data (duty point) | Impeller design   |
|------------------------------|-----------------------------|-------------------|
| Flow 0 US g.p.m.             | Flow                        | Impeller R 0 inch |
| Head 0 ft                    | Head                        | Frequency 60 Hz   |
| Static head 0 ft             |                             | Speed 3500 rpm    |

Power data referred to:  
Water [100%] ; 39.2°F; 62.4lb/ft³; 1.69E-5ft²/s  
Performance according to ANSI/HI 14.6 - Grade 2B








|              |             |            |
|--------------|-------------|------------|
| Customer     | Date        | 30.06.2021 |
| Contact      | Project     |            |
| Phone number | Project no. |            |
| Email        |             |            |

## HVL3D3-10SV6GG4F60-G

### Drawing



TechnoForce e-HV Dimensions 10SV



Di

|    |                                  |  |  |  |  |        |
|----|----------------------------------|--|--|--|--|--------|
| A  | 14 <sup>9</sup> / <sub>16</sub>  |  |  |  |  | Weight |
| B  | 17 <sup>5</sup> / <sub>16</sub>  |  |  |  |  | 872 lb |
| C  | 39 <sup>3</sup> / <sub>16</sub>  |  |  |  |  |        |
| D  | 42 <sup>11</sup> / <sub>16</sub> |  |  |  |  |        |
| H  | 6 <sup>11</sup> / <sub>16</sub>  |  |  |  |  |        |
| H1 | 46                               |  |  |  |  |        |
| H2 | 38 <sup>5</sup> / <sub>16</sub>  |  |  |  |  |        |
| L  | 44 <sup>7</sup> / <sub>16</sub>  |  |  |  |  |        |
| MD | 3                                |  |  |  |  |        |