

22SVI0303GH4F6S0

Technical data

Company Name
Contact
Phone number
E-Mail address

Operating data

1	Pumpe type	Single head pump	Fluid	Water
2	No. of pumps	1	Operating temperature t A	°F 39.2
3	Nominal flow	US g.p.m. 0	Max/Min Operating Temperature	°F /
4	Nominal head	ft 0	pH-value at t A	7
5	Static head	ft 0	Density at t A	lb/ft³ 62.4
6	Inlet pressure	psi 0	Kin. viscosity at t A	ft²/s 1.689E-5
7	Environmental temperature	°F 68	Vapor pressure at t A	psi 14.5
8	Available system NPSH	ft 0	Altitude	0

Pump data

9	Design	Multi-Stage Pumps		
10	Impellers	3	Impeller Ø	Max. inch 0.000
11	Total stages	3		designed
12	Blank stages	0		Min. inch 0.000
13	Operating speed	rpm 3500		Nominal US g.p.m.
14	Discharge flange	2" Female NPT	Flow	Max- US g.p.m. 148
15	Max. casing pressure	psi		Min- US g.p.m.
16	Max. working pressure	psi 91.1		Nominal ft
17	Impeller type	Enclosed	Head	at Qmax ft 104.6
18	Head H(Q=0)	ft 210		at Qmin ft 210.1
19	Max. shaft power	hp 7	Shaft power	hp
20	Pump weight	kg 45.9 lb	Efficiency	%
21	Total weight	lb 146.9	NPSH 3%	ft

Materials

22		Pump		Mechanical seal
23	1 - Discharge Head - Motor Adapter	Cast iron / ASTM Class 35	[S] = e-SVI Standard seal (coupled)	
24	2 - Impeller	Stainless steel / AISI 304	e-SVI Coupled seal	
25	3 - Diffuser	Stainless steel / AISI 304	Mechanical seal diameter	
26	4 - Casing	Stainless steel / AISI 316L	1 - Rotating part	Silicon carbide
27	5 - Shaft	Stainless steel / AISI 316	2 - Stationary part	Resin impregnated carbon
28	6 - Suction Base	Stainless steel / ASTM CF8M (AISI 316 cast)	3 - Elastomers	FKM
29	7 - Strainer	Stainless steel / AISI 316	4 - Springs	AISI 316
30	8 - Coupling	Aluminium	5 - Other components	AISI 316
31	9 - Seal Housing	Stainless steel / ASTM CF8M (AISI 316 cast)		
32	10 - Mechanical Seal	Refer Mechanical Seal		
33	11 - Cartridge Seal	Refer Mechanical Seal		
34	12 - Elastomers	Refer Mechanical Seal		
35	13 - Coupling Guard	Stainless steel / AISI 304		
36	14 - Shaft Sleeve and Bushing	Tungsten carbide		
37	15 - Tie Rods	Stainless steel / AISI 316		
38	16 - Screws	Stainless steel / AISI 316		
39	17 - Inducer	Stainless steel / ASTM CF8M (AISI 316 cast)		
40				
41				

Motor data

42	Manufacturer	Baldor		
43	Specific design	3ph TEPE		
44	Type	208-230/460V 184TC (V11A32E5BD2S)		
45	Rated power	7.5 hp	Item no.	
46	Nominal speed	3500 rpm	Service factor	1.15
47	Frame size	184TC	Electric data	460 V 8.4 A
48	Weight	lb 101.0	Shaft diameter	0.0 mm

Remarks

Project	Project ID	Created by	Created on	Last update
			03-02-22	03-02-22

22SVI0303GH4F6S0

Performance Curve


Company Name
Contact
Phone number
E-Mail address

	Ø inch	Delivered Flow Application Range			Lift Capability		Shaft Power P2			Frequency		60
		Min. US g.p.m.	Max. US g.p.m.	η Max. US g.p.m.	H(Q=0) ft	η Max. ft	P2(Q=0) hp	Max. hp	η Max. hp	Operating speed rpm	Hz	
Is	0.000	0	148	98.3	210	175	0.0308	7.05	6.06	Nominal flow	US g.p.m.	0
Min.	0.000	/	/	98.3	210	175	0.0308	/	6.06	Nominal head	ft	0
Max.	0.000	/	/	98.3	210	175	0.0308	/	6.06	Inlet pressure	psi	0
										Static head	ft	0

Power data referred to:

Hydr. performance acceptance acc. to EN ISO 9906 Class

Water [100%] ; 39.2°F; 62.4lb/ft³; 1.69E-5ft²/s




Project	Project ID	Created by	Created on 03-02-22	Last update 03-02-22
---------	------------	------------	------------------------	-------------------------

22SVI0303GH4F6S0

Dimensions

Company Name
Contact
Phone number
E-Mail address

22 e-SVI DIMENSIONS



Dimensions [inch]

D1	$8\frac{7}{8}$
D2	$9\frac{1}{16}$
L	$33\frac{1}{2}$
L1	$10\frac{3}{8}$
L2	$15\frac{7}{16}$
L3	$7\frac{5}{8}$

Weight (+/- 5%)

Pump	46 lb
Motor	101 lb
Blank stages	0
Total weight	147 lb

Weight table for blank stages

1-3SVI	0.44 lb per stage
5SVI	0.53 lb per stage
10SVI	1.26 lb per stage
15-22SVI	1.74 lb per stage

Dimensions and weight without obligation

Project	Project ID	Created by	Created on 03-02-22	Last update 03-02-22
---------	------------	------------	------------------------	-------------------------